

4,4,4-Trifluorobutyronitrile Safety Data Sheet 3137344 according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 01/04/2018 Version: 1.0

1.1. Identification	
Product form	: Substance
Substance name	: 4,4,4-Trifluorobutyronitrile
CAS No	: 690-95-9
Product code	: 3137-3-44
Formula	: C4H4F3N
Synonyms	: 4-Cyano-1,1,1-trifluoropropane
Other means of identification	: MFCD02183570
1.2. Relevant identified use	ses of the substance or mixture and uses advised against
Use of the substance/mixture	: Laboratory chemicals Manufacture of substances Scientific research and development
1.3. Details of the supplier	r of the safety data sheet
SynQuest Laboratories, Inc. P.O. Box 309 Alachua, FL 32615 - United States T (386) 462-0788 - F (386) 462-70 info@synquestlabs.com - www.sy	7097 <u>ynquestlabs.com</u>
1.4. Emergency telephone	
Emergency number	: (844) 523-4086 (3E Company - Account 10069)
SECTION 2: Hazard(s) ide	entification
2.1. Classification of the su	
Classification (GHS-US)	
Skin Irrit. 2H315Eye Irrit. 2AH319	 Toxic if inhaled Causes skin irritation Causes serious eye irritation May cause respiratory irritation May cause respiratory irritation
2.2. Label elements	
GHS-US labeling	
street of the st	
Hazard pictograms (GHS-US)	GHS02 GHS06 GHS07
Hazard pictograms (GHS-US) Signal word (GHS-US)	GHS02 GHS06 GHS07 CHS02 GHS06 GHS07
Hazard pictograms (GHS-US) Signal word (GHS-US) Hazard statements (GHS-US)	 GHS02 GHS02 GHS06 GHS07 3. Danger 3. H226 - Flammable liquid and vapor H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled H315 - Causes skin irritation H319 - Causes serious eye irritation H335 - May cause respiratory irritation

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P280 - Wear protective gloves/protective clothing/eye protection/face protection P301+P310 - If swallowed: Immediately call a poison center/doctor/... P302+P352 - If on skin: Wash with plenty of soap and water P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P311 - Call a POISON CENTER or doctor/physician P312 - Call a POISON CENTER or doctor/physician if you feel unwell P321 - Specific treatment (see supplemental first aid instructions on this label) P330 - Rinse mouth P332+P313 - If skin irritation occurs: Get medical advice/attention P337+P313 - If eye irritation persists: Get medical advice/attention P361 - Take off immediately all contaminated clothing P362+P364 - Take off contaminated clothing and wash it before reuse P363 - Wash contaminated clothing before reuse P370+P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish P403+P233 - Store in a well-ventilated place. Keep container tightly closed P403+P235 - Store in a well-ventilated place. Keep cool P405 - Store locked up P501 - Dispose of contents/container to an approved waste disposal plant

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

: Mono-constituent Substance type **Product identifier** % Classification (GHS-US) Name 4,4,4-Trifluorobutyronitrile (CAS No) 690-95-9 <= 100 Flam. Liq. 3, H226 (Main constituent) Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335

Full text of H-phrases: see section 16

3.2. Mixture Not applicable

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general	 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Move the affected personnel away from the contaminated area.
First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Get immediate medical advice/attention.
First-aid measures after skin contact	: Wash with plenty of soap and water. Get immediate medical advice/attention.
First-aid measures after eye contact	Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
First-aid measures after ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get immediate medical advice/attention.
4.2. Most important symptoms and effects	s, both acute and delayed
Symptoms/injuries :	The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.
4.3. Indication of any immediate medical a	ttention and special treatment needed

Treat symptomatically.

SECTI	ON 5: Firefighting measures	
5.1.	Extinguishing media	
Suitable	extinguishing media	 Alcohol resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing media appropriate for surrounding fire.

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.2. Special hazards arising from the substance or mixture		
Fire hazard		: Thermal decomposition generates: Carbon oxides. Hydrogen fluoride. Nitrogen oxides.
Explosion haza	ard	: Risk of explosion if heated under confinement. Use water spray or fog for cooling exposed containers. May form flammable/explosive vapor-air mixture.
5.3. Adv	ice for firefighters	
Firefighting ins	structions	: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.
Protection duri	ing firefighting	: Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 6: Accidental release measures	
6.1. Personal precautions, protective e	equipment and emergency procedures
General measures	: Evacuate unnecessary personnel. Ensure adequate air ventilation. Do not breathe gas, fumes, vapor or spray.
6.1.1. For non-emergency personnel	
Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene.
6.1.2. For emergency responders	
Protective equipment	Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of ignition.
6.2. Environmental precautions	
Avoid release to the environment. Notify authorities if product enters sewers or public waters.	
6.3. Methods and material for containing	nent and cleaning up
For containment	: Stop leak if safe to do so. Dike for recovery or absorb with appropriate material.

For containment	: Stop leak it safe to do so. Dike for recovery or absorb with appropriate material.
Methods for cleaning up	: Take up large spills with pump or vacuum and finish with dry chemical absorbent. Use explosion-proof equipment. Take up small spills with dry chemical absorbent. Sweep or shovel spills into appropriate container for disposal. Ventilate area.
Other information	: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

6.4. **Reference to other sections**

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Additional hazards when processed	: Handle empty containers with care because residual vapors are flammable.
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be followed. Use only non-sparking tools.
Hygiene measures	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, includi	ng any incompatibilities
Technical measures	: Comply with applicable regulations.
Storage conditions	: Keep container closed when not in use. Keep away from ignition sources. Moisture sensitive. Keep contents under inert gas.
Incompatible materials	: Refer to Section 10 on Incompatible Materials.
Storage temperature	: 2 - 8 °C Use explosion proof refrigerator
Storage area	: Store in dry, well-ventilated area.

SECTION 8: Exposure controls/personal protection

8.1. **Control parameters**

No additional information available

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Exposure controls	
Appropriate engineering controls	: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
Hand protection	: Protective gloves. 29 CFR 1910.138: Hand Protection.
Eye protection	: Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection.
Other information	: Safety shoes. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and c	hemical properties
Physical state	: Liquid
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
рН	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 139 - 140 °C
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 1.21 g/ml (@ 25 °C)
Molecular mass	: 123.0765 g/mol
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
9.2. Other information	
Refractive index	: 1.565 (@ 25 °C)

SECH	IN TU: Stability and reactivity
10.1.	Reactivity
No additio	onal information available
10.2.	Chemical stability
The produ	uct is stable at normal handling and storage conditions.
10.3.	Possibility of hazardous reactions
No additio	onal information available
10.4.	Conditions to avoid
Keep awa	ay from heat, sparks and flame.
10.5.	Incompatible materials
Strong ac	ids. Strong oxidizing agents.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

: Oral: Toxic if swallowed. Dermal: Toxic in contact with skin. Inhalation: Toxic if inhaled.

4,4,4-Trifluorobutyronitrile (690-95-9)	
ATE US (oral)	100.000 mg/kg body weight
ATE US (dermal)	300.000 mg/kg body weight
ATE US (gases)	700.000 ppmV/4h
ATE US (vapors)	3.000 mg/l/4h
ATE US (dust, mist)	0.500 mg/l/4h
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Overexposure to this material may result in methemoglobinemia. Cyanosis may occur (lips and fingernails turn blue).
SECTION 12: Ecological informatior	
12.1. Toxicity	
No additional information available	
12.2. Persistence and degradability	
No additional information available	
12.3. Bioaccumulative potential	
No additional information available	
12.4. Mobility in soil	
No additional information available	

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations		
13.1. Waste treatment methods		
Waste treatment methods	: Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.	
Waste disposal recommendations Additional information	 Dispose of contents/container in accordance with licensed collector's sorting instructions. Recycle the material as far as possible. 	
SECTION 44. Transport information	· · ·	
SECTION 14: Transport information		
Department of Transportation (DOT)		
In accordance with DOT Transport document description	: UN3273 Nitriles, flammable, toxic, n.o.s., 3, II	
Hansport document description		

01/04/2018

: Nitriles, flammable, toxic, n.o.s.

: UN3273

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT) : 3 - Fianmable liquid Packing group (DOT) : II - Medium Danger DOT Packaging Non Buk (49 CFR 173.xxx) : 202 DOT Spackaging Buk (49 CFR 173.xxx) : 202 DOT Spackaging Buk (49 CFR 173.xxx) : 202 DOT Spackaging Buk (49 CFR 173.xxx) : 202 DT Spackaging Exceptions (49 CFR 173.xxx) : 15 178 274(9)(2) Normal	Transport hazard class(es) (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT) : I.I. Medium Danger DOT Packaging Non Bulk (49 CFR 173.xxx) : 202 DOT Sphools : 2.43 DOT Sphools : 6 Identifies PSN requiring a technical name DOT Sphools : 6 Identifies PSN requiring a technical name DOT Sphool : 182 - Authorized IBCE: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite 105 (31H21). Additional Requirement. Only liquids with a vapor pressure loss than or equal to 10 (shortar integrature during transport, 11 is of 182.734(2)(2) Normal	Hazard labels (DOT)	
DOT Packaging Non Buk (49 CFR 173.xxx) : 243 DOT Synebils : G - Identifies PSN requiring a technical name DOT Synebils : G - Identifies PSN requiring a technical name DOT Synebils : B2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31H2); Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 120 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T1 - 6 178.275 (0)(3) TP2 - a, The maximum degree of filing must not exceed the degree of filing determined by the temperature during transport, if is the temperature during transport if is the temperature during transport if is described by the activited test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP. DOT Packaging Exceptions (49 CFR 173.xxx) : 150 DOT Quantity Limitations Passenger aircraft/rail : 1. L QG CR 173.27) :		6.1 - Poison
DOT Packaging Non Buk (49 CFR 173.xxx) : 243 DOT Synebils : G - Identifies PSN requiring a technical name DOT Synebils : G - Identifies PSN requiring a technical name DOT Synebils : B2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31H2); Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 120 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T1 - 6 178.275 (0)(3) TP2 - a, The maximum degree of filing must not exceed the degree of filing determined by the temperature during transport, if is the temperature during transport if is the temperature during transport if is described by the activited test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP. DOT Packaging Exceptions (49 CFR 173.xxx) : 150 DOT Quantity Limitations Passenger aircraft/rail : 1. L QG CR 173.27) :		
DOT Packaging Non Buk (49 CFR 173.xxx) : 243 DOT Synebils : G - Identifies PSN requiring a technical name DOT Synebils : G - Identifies PSN requiring a technical name DOT Synebils : B2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31H2); Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 120 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T1 - 6 178.275 (0)(3) TP2 - a, The maximum degree of filing must not exceed the degree of filing determined by the temperature during transport, if is the temperature during transport if is the temperature during transport if is described by the activited test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP. DOT Packaging Exceptions (49 CFR 173.xxx) : 150 DOT Quantity Limitations Passenger aircraft/rail : 1. L QG CR 173.27) :		
DOT Packaging Non Buk (49 CFR 173.xxx) : 243 DOT Synebils : G - Identifies PSN requiring a technical name DOT Synebils : G - Identifies PSN requiring a technical name DOT Synebils : B2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31H2); Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 120 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T1 - 6 178.275 (0)(3) TP2 - a, The maximum degree of filing must not exceed the degree of filing determined by the temperature during transport, if is the temperature during transport if is the temperature during transport if is described by the activited test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP. DOT Packaging Exceptions (49 CFR 173.xxx) : 150 DOT Quantity Limitations Passenger aircraft/rail : 1. L QG CR 173.27) :		
DOT Packaging Bulk (49 CFR 173.xx) : 23 DOT Symbols : G - Identifies PSN requiring a technical name DOT Special Provisions (49 CFR 172.122) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31H21). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 ber at 125 P); or 130 KPa at 55 C (1.3 ber at 135 P); are authorized. DT Special Provisions (49 CFR 172.122) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31H21). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 cubical expansion of the liquid during filling, and a is the mac non-finication of cubical expansion of the liquid between the mean temperature during filling, and a is the mac non-finication of cubical expansion of the liquid between the mean coefficient of cubical expansion of the liquid between the mean coefficient of cubical expansion of the liquid between the mean coefficient of cubical expansion of the liquid between the mean coefficient of cubical expansion of the liquid at 50 C (12P); respectively. DT Packaging Exceptions (49 CFR 172.xx) : 150 DOT Quantity Limitations Passenger aircraftrial : 11. Qid QFR 172.27) : 00 Cl (2P); respectively. DT Vessel Stowage Location : 8 - 00. The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passenger suble liquid (02(R) (172, 2P)); Passenger vessel carrying a number of passenger suble liquid (02(R) (172, 2P)); Passenger vessel carrying a number of passenger suble liquid (02(R) (172, 2P)); Pass		-
DOT Symbols : G - Identifies PSN requiring a technical name DOT Special Provisions (49 CFR 172.102) : B2- Authorazed IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H and 31H2); Composite (31H 21); Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.5 bar at 13 F) are authorized. 111 6 of 172, 2 a. The maximum degree of filing must not exceed the degree of filing determined by the following: (Image) Where: It is the maximum mean bulk temperature during transport, If is the temperature modify transport, If is the temperature modify transport, If is the temperature modify transporting (n) both in degrees of filing determined by the following: (Image) Where: If is and 600 are the densities (n) multis of mass per unit volume) of the liquid at 15 C (56 F) and 50 C (122 F), respectively. DOT Packaging Exceptions (49 CFR 173.xxx) : 150 DOT Quantity Limitations Passenger aircraft only (4) : 60 L CFR 173.27) : 150 DOT Quantity Limitations Cargo aircraft only (4) : 60 L CFR 175.76) : 8 - (1) The material may be stowed 'on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passenger specified in paragraph (k)(2)(i) of this section a veceeded. DOT Vessel Stowage Location : 8 - (1) The material may be stowed 'on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passenger specified in paragraph (k)(2)(i) of this section is veceeded. DOT Vessel Stowage Location : 8 - (1) The material may be stowed 'on deck" or "under deck" on a cargo ves	00 ()	
DOT Special Provisions (49 CFR 172.102) : B2- Authorized BC2: Metal (31A, 31B and 31N): Right Subt a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bur at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. 1711 - 6 116274(d)(2) Normal mean bulk temperature during transport, fit is the following: (image) Where: it is the maximum mean bulk temperature during transport, fit is the maximum mean bulk temperature during transport, fit is the maximum mean bulk temperature during transport, fit is the maximum mean bulk temperature during transport, fit is the maximum mean bulk temperature during transport, fit is the maximum mean bulk temperature during transport, fit is the maximum mean bulk temperature during transport, fit is the subtransmort during transport during during during during during during during during d		
(11H21). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 12P, or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T11 - 6 178.274(d)(2) Normal	-	
(49 CFR 173.27)DOT Quantity Limitations Cargo aircraft only (49: 60 LCFR 175.75): B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passenger vessel is which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.DOT Vessel Stowage Other: 40 - Stow "clear of living quarters",52 - Stow "separated from" acidsOther information: No supplementary information available.TDG No additional information available:Transport by sea UN-No. (IMDG): 3273Proper Shipping Name (IMDG): NITRILES, FLAMMABLE, TOXIC, N.O.S.Class (IMDG): 1 - substances presenting medium dangerAir transport UN-No. (IATA): 3273Proper Shipping Name (IATA): 3 - Flammable, toxic, n.o.s.Class (IATA): 3 - Flammable, toxic, n.o.s.C	DOT Packaging Exceptions (49 CFR 173.xxx)	 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T11 - 6 178.274(d)(2) Normal
(49 CFR 173.27)DOT Quantity Limitations Cargo aircraft only (49: 60 LCFR 175.75): B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passenger vessel is which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.DOT Vessel Stowage Other: 40 - Stow "clear of living quarters",52 - Stow "separated from" acidsOther information: No supplementary information available.TDG No additional information available:Transport by sea UN-No. (IMDG): 3273Proper Shipping Name (IMDG): NITRILES, FLAMMABLE, TOXIC, N.O.S.Class (IMDG): 1 - substances presenting medium dangerAir transport UN-No. (IATA): 3273Proper Shipping Name (IATA): 3 - Flammable, toxic, n.o.s.Class (IATA): 3 - Flammable, toxic, n.o.s.C	001 (
CFR 175.75) E DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded. DOT Vessel Stowage Other : 40 - Stow "clear of living quarters",52 - Stow "separated from" acids Other information : No supplementary information available. TDC No additional information available Transport by sea		
passenger vessel carrying a number of passengers limited to not more than the larger of 25 passenger, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.DOT Vessel Stowage Other: 40 - Stow "clear of living quarters",52 - Stow "separated from" acidsOther information: No supplementary information available.TDG No additional information available.Transport by sea UN-No. (IMDG): 3273Proper Shipping Name (IMDG): 3 - Flammable liquidsPacking group (IMDG): 1 - substances presenting medium dangerAir transport UN-No. (IATA): 3273Proper Shipping Name (IATA): 3 - Flammable, toxic, n.o.s.Class (IATA): 3 - Flammable, toxic, n.o.s.	CFR 175.75)	
Other information: No supplementary information available.TDG No additional information availableTransport by seaUN-No. (IMDG): 3273Proper Shipping Name (IMDG): NITRILES, FLAMMABLE, TOXIC, N.O.S.Class (IMDG): 3 - Flammable liquidsPacking group (IMDG): 11 - substances presenting medium dangerAir transportUN-No. (IATA): 3273Proper Shipping Name (IATA): Nitriles, flammable, toxic, n.o.s.Class (IATA): 3 - Flammable tiquids	DOT Vessel Stowage Location	passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph $(k)(2)(i)$ of this
TDG No additional information available Transport by sea UN-No. (IMDG) : 3273 Proper Shipping Name (IMDG) : NITRILES, FLAMMABLE, TOXIC, N.O.S. Class (IMDG) : 3 - Flammable liquids Packing group (IMDG) : II - substances presenting medium danger Air transport UN-No. (IATA) UN-No. (IATA) : 3273 Proper Shipping Name (IATA) : 3273 Proper Shipping Name (IATA) : 3273 Proper Shipping Name (IATA) : 3273	DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters",52 - Stow "separated from" acids
No additional information availableTransport by seaUN-No. (IMDG): 3273Proper Shipping Name (IMDG): NITRILES, FLAMMABLE, TOXIC, N.O.S.Class (IMDG): 3 - Flammable liquidsPacking group (IMDG): 1 - substances presenting medium dangerAir transportUN-No. (IATA): 3273Proper Shipping Name (IATA): Nitriles, flammable, toxic, n.o.s.Class (IATA): 3 - Flammable Liquids	Other information	: No supplementary information available.
Transport by seaUN-No. (IMDG): 3273Proper Shipping Name (IMDG): NITRILES, FLAMMABLE, TOXIC, N.O.S.Class (IMDG): 3 - Flammable liquidsPacking group (IMDG): 1 - substances presenting medium dangerAir transportImage: Class (IATA)UN-No. (IATA): 3273Proper Shipping Name (IATA): Nitriles, flammable, toxic, n.o.s.Class (IATA): 3 - Flammable Liquids	TDG	
UN-No. (IMDG): 3273Proper Shipping Name (IMDG): NITRILES, FLAMMABLE, TOXIC, N.O.S.Class (IMDG): 3 - Flammable liquidsPacking group (IMDG): II - substances presenting medium dangerAir transportUN-No. (IATA): 3273Proper Shipping Name (IATA): 3273Class (IATA): Nitriles, flammable, toxic, n.o.s.Class (IATA): 3 - Flammable Liquids	No additional information available	
Proper Shipping Name (IMDG): NITRILES, FLAMMABLE, TOXIC, N.O.S.Class (IMDG): 3 - Flammable liquidsPacking group (IMDG): II - substances presenting medium dangerAir transportUN-No. (IATA): 3273Proper Shipping Name (IATA): Nitriles, flammable, toxic, n.o.s.Class (IATA): 3 - Flammable Liquids	Transport by sea	
Class (IMDG): 3 - Flammable liquidsPacking group (IMDG): II - substances presenting medium dangerAir transport	UN-No. (IMDG)	: 3273
Packing group (IMDG): II - substances presenting medium dangerAir transportUN-No. (IATA): 3273Proper Shipping Name (IATA): Nitriles, flammable, toxic, n.o.s.Class (IATA): 3 - Flammable Liquids	Proper Shipping Name (IMDG)	: NITRILES, FLAMMABLE, TOXIC, N.O.S.
Air transport UN-No. (IATA) : 3273 Proper Shipping Name (IATA) : Nitriles, flammable, toxic, n.o.s. Class (IATA) : 3 - Flammable Liquids	Class (IMDG)	: 3 - Flammable liquids
UN-No. (IATA): 3273Proper Shipping Name (IATA): Nitriles, flammable, toxic, n.o.s.Class (IATA): 3 - Flammable Liquids	Packing group (IMDG)	: II - substances presenting medium danger
Proper Shipping Name (IATA): Nitriles, flammable, toxic, n.o.s.Class (IATA): 3 - Flammable Liquids	Air transport	
Class (IATA) : 3 - Flammable Liquids	UN-No. (IATA)	: 3273
	Proper Shipping Name (IATA)	: Nitriles, flammable, toxic, n.o.s.
Packing group (IATA) : II - Medium Danger	Class (IATA)	: 3 - Flammable Liquids
	Packing group (IATA)	: II - Medium Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4,4,4-Trifluorobutyronitrile CAS No 690-9	5-9 100%	

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

SECTION 16: Other information

Full text of H-phrases:

text of 11 philases.	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhalation) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 3	Flammable liquids Category 3
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H226	Flammable liquid and vapor
H301	Toxic if swallowed
H311	Toxic in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H331	Toxic if inhaled
H335	May cause respiratory irritation

NFPA health hazard	: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.
NFPA fire hazard	: 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.
HMIS III Rating	
Health	: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given
Flammability	2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F but below 200 F. (Classes II & IIIA)
Physical	: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.
SDS US (GHS HazCom 2012)	

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.