

# **Material Safety Data Sheet**

Transportation Emergency: 1-800-451-8346

Date last revised: August 25, 2014 Date printed: August 25, 2014

# SECTION 1. ----- CHEMICAL IDENTIFICATION-----

CATALOG #: 3H31-3-08

NAME: 5-(TRIFLUOROMETHYL)-1H-INDOLE SYNONYM: 5-(TRIFLUOROMETHYL)INDOLE

# SECTION 2. ---- COMPOSITION/INFORMATION ON INGREDIENTS -----

CAS NUMBER: 100846-24-0 MDL NUMBER: MFCD03095341 MOLECULAR FORMULA: C<sub>9</sub>H<sub>6</sub>F<sub>3</sub>N MOLECULAR WEIGHT: 185.15

#### SECTION 3. ----- HAZARDS IDENTIFICATION -----

LABEL PRECAUTIONARY STATEMENTS

TOXIC.

TOXIC IF SWALLOWED.

IRRITANT.

IRRITATING TO EYES, RESPIRATORY SYSTEM AND SKIN.

# SECTION 4. ----- FIRST-AID MEASURES-----

## ORAL EXPOSURE

IF SWALLOWED, WASH OUT MOUTH WITH WATER PROVIDED PERSON IS CONSCIOUS. CALL A PHYSICIAN.

# INHALATION EXPOSURE

IF INHALED, REMOVE TO FRESH AIR. IF NOT BREATHING GIVE

ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN.

## DERMAL EXPOSURE

IN CASE OF CONTACT, IMMEDIATELY WASH SKIN WITH SOAP AND COPIOUS AMOUNTS OF WATER.

#### EYE EXPOSURE

IN CASE OF CONTACT, IMMEDIATELY FLUSH EYES WITH COPIOUS AMOUNTS OF WATER FOR AT LEAST 15 MINUTES.

## SECTION 5. ----- FIRE FIGHTING MEASURES -----

#### FLASHPOINT

NOT ESTABLISHED

#### EXTINGUISHING MEDIA

SUITABLE: FOR SMALL (INCIPIENT) FIRES, USE MEDIA SUCH AS "ALCOHOL" FOAM, DRY CHEMICAL, OR CARBON DIOXIDE. FOR LARGE FIRES, APPLY WATER FROM AS FAR AS POSSIBLE. USE VERY LARGE QUANTITIES (FLOODING) OF WATER APPLIED AS A MIST OR SPRAY; SOLID STREAMS OF WATER MAY BE INEFFECTIVE. COOL ALL AFFECTED CONTAINERS WITH FLOODING OUANTITIES OF WATER.

#### **FIREFIGHTING**

PROTECTIVE EQUIPMENT: WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING TO PREVENT CONTACT WITH SKIN AND EYES. SPECIFIC HAZARD(S): EMITS TOXIC FUMES UNDER FIRE CONDITIONS.

# SECTION 6. ----- ACCIDENTAL RELEASE MEASURES-----

#### PERSONAL PROTECTION

AVOID BREATHING VAPOR MIST, OR GAS. ENSURE ADEQUATE VENTILATION. WEAR PROTECTIVE EQUIPMENT INCLUDING RUBBER GLOVES, AND EYE PROTECTION. KEEP UNPROTECTED PERSONS AWAY.

REMOVE ALL SOURCES OF IGNITION. BEWARE OF VAPORS ACCUMULATING TO FORM EXPLOSIVE CONCENTRATIONS. VAPORS CAN ACCUMULATE IN LOW AREAS.

#### ENVIRONMENTAL PROTECTION

PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. TAKE PRECAUTIONS TO ENSURE PRODUCT DOES NOT CONTAMINATE THE GROUND OR ENTER THE DRAINAGE SYSTEM.

### **COLLECTION**

CONTAIN SPILLAGE, AND THEN COLLECT WITH AN ELECTRICALLY PROTECTED VACUUM CLEANER OR BY WET-BRUSHING AND PLACE IN CONTAINER FOR DISPOSAL ACCORDING TO LOCAL REGULATIONS.

## SECTION 7. ----- HANDLING AND STORAGE-----

## HANDLING

TEMPERATURE: 2 - 8 °C.

USER EXPOSURE: AVOID INHALATION. AVOID CONTACT WITH EYES, SKIN, AND CLOTHING. AVOID PROLONGED OR REPEATED EXPOSURE.
USE EXPLOSION-PROOF EQUIPMENT. KEEP AWAY FROM SOURCES OF IGNITION. TAKE MEASURES TO PREVENT THE BUILD UP OF ELECTROSTATIC CHARGE.
STORAGE

SUITABLE: TIGHTLY CLOSED CONTAINERS IN A DRY AND WELL-VENTILATED PLACE. CONTAINERS WHICH ARE OPENED MUST BE CAREFULLY RESEALED AND KEPT UPRIGHT TO PREVENT LEAKAGE. STORE IN COOL, DRY PLACE. STORE UNDER INERT GAS. AVOID DIRECT SUNLIGHT. RECOMMENDED STORAGE

## SECTION 8. ----- EXPOSURE CONTROLS/PERSONAL PROTECTION-----

#### **ENGINEERING CONTROLS**

SAFETY SHOWER AND EYE BATH. MECHANICAL EXHAUST REQUIRED.

## PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY: USE RESPIRATORS AND COMPONENTS TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR CEN (EU). WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING RESPIRATORS ARE APPROPRIATE USE A FULL-FACE RESPIRATOR WITH MULTI-PURPOSE COMBINATION (US) OR TYPE ABEK (EN 14387) RESPIRATOR CARTRIDGES AS A BACKUP TO ENGINEERING CONTROLS. IF THE RESPIRATOR IS THE SOLE MEANS OF PROTECTION, USE A FULL-FACE SUPPLIED AIR RESPIRATOR. HAND: COMPATIBLE CHEMICAL-RESISTANT GLOVES.

EYE: CHEMICAL SAFETY GOGGLES.

#### GENERAL HYGIENE MEASURES

WASH CONTAMINATED CLOTHING BEFORE REUSE. WASH THOROUGHLY AFTER HANDLING.

## SECTION 9. ----- PHYSICAL AND CHEMICAL PROPERTIES -----

APPEARANCE AND ODOR

SOLID

PHYSICAL PROPERTIES

MELTING POINT: 67-70°C

#### SECTION 10. -----STABILITY AND REACTIVITY -----

# **STABILITY**

STABLE: STABLE UNDER RECOMMENDED STORAGE CONDITIONS.

MATERIALS TO AVOID: STRONG OXIDIZING AGENTS, STRONG ACIDS AND BASES.

CONDITIONS TO AVOID: HEAT, FLAMES AND SPARKS, EXTREMES OF TEMPERATURE, AND DIRECT SUNLIGHT.

### HAZARDOUS DECOMPOSITION PRODUCTS

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON OXIDES, HYDROGEN FLUORIDE, NITROGEN OXIDES.

## HAZARDOUS POLYMERIZATION

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

## SECTION 11. ----- TOXICOLOGICAL INFORMATION -----

#### ROUTE OF EXPOSURE

INHALATION: HARMFUL IF INHALED. CAUSES RESPIRATORY TRACT IRRITATION.

INGESTION: HARMFUL IF SWALLOWED.

SKIN: HARMFUL IF ABSORBED THROUGH SKIN. CAUSES SKIN IRRITATION.

EYES: CAUSES EYE IRRITATION.

## SIGNS AND SYMPTOMS OF EXPOSURE

TO THE BEST OF OUR KNOWLEDGE, THE TOXICOLOGICAL PROPERTIES OF THIS PRODUCT HAVE NOT BEEN FULLY DETERMINED.

# SECTION 12. ----- ECOLOGICAL INFORMATION -----DATA NOT YET AVAILABLE. SECTION 13. ----- DISPOSAL CONSIDERATIONS -----APPROPRIATE METHOD OF DISPOSAL OF SUBSTANCE OR PREPARATION THIS COMBUSTIBLE MATERIAL MAY BE BURNED IN A CHEMICAL INCINERATOR EQUIPPED WITH AN AFTERBURNER AND SCRUBBER. OBSERVE ALL FEDERAL, STATE, AND LOCAL ENVIRONMENTAL REGULATIONS. SECTION 14. ----- TRANSPORT INFORMATION -----UN2811 - HC 6.1 - PG III SECTION 15. ----- REGULATORY INFORMATION -----EU ADDITIONAL CLASSIFICATION SYMBOL OF DANGER: T, Xi INDICATION OF DANGER: TOXIC. IRRITANT. RISK STATEMENTS: 25-36/37/38 SAFETY STATEMENTS: 22-24/25-26-36/37/39-45 US CLASSIFICATION AND LABEL TEXT TSCA: NOT LISTED ON TSCA INVENTORY; FOR R&D USE ONLY SECTION 16. ----- OTHER INFORMATION-----

THE ABOVE INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. SYNQUEST LABS, INC. SHALL NOT BE HELD LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING OR FROM CONTACT WITH THE ABOVE PRODUCT.