

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations SDS ID: 51813X0

Issue date: 06.12.2017 Revision date: 18.12.2023 Version: 1.1

SECTION 1: Identification

1.1. Identification

Product form : Substance

Substance name : Trimethyl(pentafluoroethyl)silane

CAS-No. : 124898-13-1
Product code : 5181-3-X0
Formula : C5H9F5Si

Synonyms : Trimethyl(perfluoroethyl)silane

Other means of identification : MFCD04116436

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Laboratory chemicals

Manufacture of substances

Scientific research and development

1.3. Supplier

SynQuest Laboratories, Inc. Inc.

P.O. Box 309

Alachua, FL, Alachua, 32615 United States of America

T (386) 462-0788 - F (386) 462-7097

info@synquestlabs.com - www.synquestlabs.com

1.4. Emergency telephone number

Emergency number : (844) 523-4086 (3E Company - Account 10069)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 2 H225 Highly flammable liquid and vapor

Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A

Specific target organ toxicity – Single exposure, Category 3,

H315

Causes skin irritation

Causes serious eye irritation

May cause respiratory irritation

Respiratory tract irritation

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)





Signal word (GHS US) : Danger

Hazard statements (GHS US) : H225 - Highly flammable liquid and vapor

H315 - Causes skin irritation H319 - Causes serious eye irritation H335 - May cause respiratory irritation

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS US)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting equipment

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P261 - Avoid breathing fumes, mist, spray, vapors.

P264 - Wash skin thoroughly after handling

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 - If on skin: Wash with plenty of soap and water

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 - Call a POISON CENTER or doctor/physician if you feel unwell

P321 - Specific treatment (see supplemental first aid instructions on this label)

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P370+P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to an approved waste disposal plant

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Substance type : Mono-constituent

Name	Product identifier	%	GHS US classification
Trimethyl(pentafluoroethyl)silane (Main constituent)	CAS-No.: 124898-13-	≤ 100	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : In case of accident or if you feel unwell, seek medical advice immediately (show the label where

possible). Move the affected personnel away from the contaminated area.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial

respiration. Get medical advice/attention.

First-aid measures after skin contact : Wash with plenty of soap and water. Get medical advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical advice/attention.

First-aid measures after ingestion : Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth

out with water. Get medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.

ana, or in occion in

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Alcohol resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing media appropriate for surrounding fire.

344.34

5.2. Specific hazards arising from the chemical

Fire hazard : Thermal decomposition generates: Carbon oxides. Hydrogen fluoride. Silicon oxides.

Explosion hazard : Risk of explosion if heated under confinement. Use water spray or fog for cooling exposed

containers. May form flammable/explosive vapor-air mixture.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection during firefighting : Wear gas tight chemically protective clothing in combination with self contained breathing

apparatus. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate unnecessary personnel. Ensure adequate air ventilation. Do not breathe gas, fumes,

vapor or spray.

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene.

6.1.2. For emergency responders

6.1.1. For non-emergency personnel

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

Emergency procedures : Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of ignition.

18.12.2023 (Revision date) EN (English US) 3/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so. Dike for recovery or absorb with appropriate material.

Methods for cleaning up : Take up large spills with pump or vacuum and finish with dry chemical absorbent. Use explosion-

proof equipment. Take up small spills with dry chemical absorbent. Sweep or shovel spills into appropriate container for disposal. Ventilate area.

Other information : For disposal of solid materials or residues refer to section 13: "Disposal considerations".

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling

: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be

followed. Use only non-sparking tools.

Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or

smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Keep container closed when not in use. Keep away from ignition sources. Moisture sensitive.

Keep contents under inert gas.

Incompatible materials : Refer to Section 10 on Incompatible Materials.

Storage area : Store in dry, cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Trimethyl(pentafluoroethyl)silane (124898-13-1)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

protective gloves. 29 CFR 1910.138: Hand Protection

Eye protection:

Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection

18.12.2023 (Revision date) EN (English US) 4/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection

Personal protective equipment symbol(s):









Other information:

Safety shoes. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : No data available
Odor : No data available
Odor threshold : No data available
pH : No data available
Melting point : No data available
Freezing point : No data available

Boiling point : $60 \, ^{\circ}\text{C}$ Flash point : $-17 \, ^{\circ}\text{C}$

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : No data available Vapor pressure : No data available Relative vapor density at 20 °C : No data available Relative density : No data available Density : 1,095 g/ml (@ 25 °C)

192,2 g/mol Molecular mass Solubility No data available Partition coefficient n-octanol/water (Log Pow) No data available Auto-ignition temperature No data available : No data available Decomposition temperature Viscosity, kinematic : No data available Viscosity, dynamic : No data available **Explosion limits** : No data available Explosive properties No data available Oxidizing properties No data available

9.2. Other information

Refractive index : 1,325 (@ 20 °C)

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Keep away from heat, sparks and flame.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

STOT-single exposure : May cause respiratory irritation.

STOT-repeated exposure : Not classified
Aspiration hazard : Not classified
Viscosity, kinematic : No data available

Symptoms/effects : The most important known symptoms and effects are described in the labelling (see section 2.2)

and/or in section 11.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

Trimethyl(pentafluoroethyl)silane (124898-13-1)

Persistence and degradability

Not readily biodegradable. May cause long-term adverse effects in the environment. PBT -

Persistent, Bioaccumulative and Toxic.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3. Bioaccumulative potential

Trimethyl(pentafluoroethyl)silane (124898-13-1)

Bioaccumulative potential

Perfluorinated alkanes (PFAs, "forever chemicals") are long lasting, widely used chemicals that break down slowly over time. The potential hazards of PFAs are under investigation and have not been established.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods

Sewage disposal recommendations

Product/Packaging disposal recommendations

Additional information

Ecology - waste materials

- : Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.
- : See the EPA's Interim Guidance on PFAS Destruction and Disposal.
- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : Recycle the material as far as possible.
- : This material is considered to be a "Forever chemical". Prevent any possible release to the environment. Do not discharge into drains. Take all necessary measures to prevent accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems, or emergency response.

SECTION 14: Transport information

14.1. UN number

DOT NA No : UN1993 UN-No. (TDG) : Not applicable UN-No. (IMDG) : 1993 UN-No. (IATA) : 1993

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Flammable liquids, n.o.s.

Proper Shipping Name (TDG) : Not applicable

Proper Shipping Name (IMDG) : FLAMMABLE LIQUID, N.O.S.
Proper Shipping Name (IATA) : Flammable liquid, n.o.s.

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 3 Hazard labels (DOT) : 3



TDG

Transport hazard class(es) (TDG) : Not applicable

18.12.2023 (Revision date) EN (English US) 7/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

IMDG

Transport hazard class(es) (IMDG) : 3
Hazard labels (IMDG) : 3



IATA

Transport hazard class(es) (IATA) : 3
Hazard labels (IATA) : 3



14.4. Packing group

Packing group (DOT) : I

Packing group (TDG) : Not applicable

Packing group (IMDG) : II
Packing group (IATA) : II

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

UN-No.(DOT) : UN1993

DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite

(31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when

the flash point of the hazardous material transported is greater than 0 C (32 F).

TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the

MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Quantity Limitations Passenger aircraft/rail (49 : 5 L

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49

CFR 175.75)

DOT Vessel Stowage Location

ED 475 75

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

TDG

No data available

18.12.2023 (Revision date) EN (English US) 8/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

IMDG

Special provision (IMDG) : 274
Limited quantities (IMDG) : 1 L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T7

Tank special provisions (IMDG) : TP1, TP28, TP8

EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS EmS-No. (Spillage) : S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER

Stowage category (IMDG) : B

IATA

PCA Excepted quantities (IATA) : E2 PCA Limited quantities (IATA) : Y341 PCA limited quantity max net quantity (IATA) : 1L PCA packing instructions (IATA) 353 PCA max net quantity (IATA) : 5L : 364 CAO packing instructions (IATA) : 60L CAO max net quantity (IATA) Special provision (IATA) : A3 ERG code (IATA) 3Н

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

Trimethyl(pentafluoroethyl)silane CAS-No. 124898-13-1 100%

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 18.12.2023

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases		
H225	Highly flammable liquid and vapor	
H315	Causes skin irritation	
H319	Causes serious eye irritation	
H335	May cause respiratory irritation	


NFPA health hazard : 3 - Materials that, under emergency conditions, can cause serious or

permanent injury.

NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

: 0 - Material that in themselves are normally stable, even under fire

conditions.



Hazard Rating

NFPA reactivity

Health

Flammability

Physical

Safety Data Sheet (SDS), USA

: 2 Moderate Hazard - Temporary or minor injury may occur

: 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB IC)

: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.