

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations SDS ID: 5681301

Issue date: 10/4/2022 Version: 1.0

### **SECTION 1: Identification**

#### 1.1. Identification

Product form : Substance

Substance name : Diphenyldifluorosilane

CAS-No. : 312-40-3
Product code : 5681-3-01
Formula : C12H10F2Si

Synonyms : Difluorodiphenylsilane
Other means of identification : MFCD00017898

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Laboratory chemicals

Manufacture of substances

Scientific research and development

### 1.3. Supplier

SynQuest Laboratories, Inc. Inc.

P.O. Box 309

Alachua, FL, Alachua, 32615 United States of America

T (386) 462-0788 - F (386) 462-7097

info@synquestlabs.com - www.synquestlabs.com

### 1.4. Emergency telephone number

Emergency number : (844) 523-4086 (3E Company - Account 10069)

### **SECTION 2: Hazard(s) identification**

#### 2.1. Classification of the substance or mixture

#### **GHS US classification**

Acute toxicity (dermal) Category 4 H312 Harmful in contact with skin

Skin corrosion/irritation Category 1B H314 Causes severe skin burns and eye damage

Serious eye damage/eye irritation Category 1 H318 Causes serious eye damage
Specific target organ toxicity – Single exposure, Category 3, H335 May cause respiratory irritation

Respiratory tract irritation

Full text of H statements : see section 16

### 2.2. GHS Label elements, including precautionary statements

### **GHS US labeling**

Hazard pictograms (GHS US)





Signal word (GHS US) : Danger

Hazard statements (GHS US) : H312 - Harmful in contact with skin

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage H335 - May cause respiratory irritation

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS US)

: P260 - Do not breathe fumes, mist, spray, vapors.

P264 - Wash skin thoroughly after handling

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 - If swallowed: rinse mouth, Do NOT induce vomiting.

P302+P352 - If on skin: Wash with plenty of soap and water

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a POISON CENTER or doctor/ physician

P321 - Specific treatment (see supplemental first aid instructions on this label)

P322 - Specific treatment (see supplemental first aid instruction on this label)

P362+P364 - Take off contaminated clothing and wash it before reuse.

P363 - Wash contaminated clothing before reuse.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P501 - Dispose of contents/container to an approved waste disposal plant

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

No additional information available

### **SECTION 3: Composition/Information on ingredients**

### 3.1. Substances

Substance type : Mono-constituent

Name	Product identifier	%	GHS US classification
Diphenyldifluorosilane (Main constituent)	CAS-No.: 312-40-3	≤ 100	Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

#### 3.2. Mixtures

Not applicable

### **SECTION 4: First-aid measures**

### 4.1. Description of first aid measures

First-aid measures general

: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Move the affected personnel away from the contaminated area.

First-aid measures after inhalation

: Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Get immediate medical advice/attention.

First-aid measures after skin contact

: Wash with plenty of soap and water. Remove contaminated clothing and shoes. In case of skin contact, wearing rubber gloves rub 2.5% calcium gluconate gel continuously into the affected area for 1.5 hours or until further medical care is available. Get immediate medical advice/attention.

10/4/2022 (Issue date) EN (English US) 2/10

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after eve contact

: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid measures after ingestion

: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get immediate medical advice/attention.

### 4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms

Symptoms/effects

Symptoms/effects after inhalation

: Absorption of excessive F- can result in acute systemic fluorosis with hypocalcemia, interference with various metabolic functions and organ damage (heart, liver, kidneys).

: The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.

: Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically. Absorption of excessive F- can result in acute systemic fluorosis with hypocalcemia, interference with various metabolic functions and organ damage (heart, liver, kidneys).

### **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media

: Alcohol resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing media appropriate for surrounding fire.

#### 5.2. Specific hazards arising from the chemical

Fire hazard

: Thermal decomposition generates: Carbon oxides. Hydrogen fluoride. Silicon oxides.

Explosion hazard

Risk of explosion if heated under confinement. Use water spray or fog for cooling exposed containers.

#### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions

: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection during firefighting

: Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Evacuate unnecessary personnel. Ensure adequate air ventilation. Do not breathe gas, fumes, vapor or spray.

#### 6.1.1. For non-emergency personnel

**Emergency procedures** 

: Only qualified personnel equipped with suitable protective equipment may intervene.

#### 6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

**Emergency procedures** 

 Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level.

### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

10/4/2022 (Issue date) EN (English US) 3/10

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 6.3. Methods and material for containment and cleaning up

For containment

: Stop leak if safe to do so. Dike for recovery or absorb with appropriate material.

Methods for cleaning up

: Take up large spills with pump or vacuum and finish with dry chemical absorbent. Use explosionproof equipment. Take up small spills with dry chemical absorbent. Sweep or shovel spills into

appropriate container for disposal. Ventilate area.

Other information : For disposal of solid materials or residues refer to section 13: "Disposal considerations".

### 6.4. Reference to other sections

No additional information available

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Precautions for safe handling

: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal

Hygiene measures

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Comply with applicable regulations.

Storage conditions

: Keep container closed when not in use. Moisture sensitive. Keep contents under inert gas.

Incompatible materials

: Refer to Section 10 on Incompatible Materials.

protective equipment. Avoid contact with skin and eyes.

Storage area

: Store in dry, cool, well-ventilated area.

### **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### Diphenyldifluorosilane (312-40-3)

No additional information available

### 8.2. Appropriate engineering controls

Appropriate engineering controls

: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

protective gloves. 29 CFR 1910.138: Hand Protection

#### Eye protection:

Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection

### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection

10/4/2022 (Issue date) EN (English US) 4/10

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Personal protective equipment symbol(s):









#### Other information:

Safety shoes. 29 CFR 1910.136: Foot Protection.

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

No data available Color Odor : No data available Odor threshold : No data available рΗ : No data available Melting point : No data available Freezing point : No data available Boiling point : 157 °C (@ 50 mm Hg) Flash point : No data available Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : No data available Vapor pressure : 5 mm Hg (@ 100 °C) Relative vapor density at 20 °C : No data available Relative density : No data available : 1.145 g/ml (@ 17 °C) Density : 220.2901 g/mol Molecular mass Solubility : No data available Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : No data available No data available Decomposition temperature

Decomposition temperature : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available Explosion limits : No data available Explosive properties : No data available Oxidizing properties : No data available

9.2. Other information

Refractive index : 1.5221 (@ 25 °C)

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

The product is stable at normal handling and storage conditions.

### 10.3. Possibility of hazardous reactions

No additional information available

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.4. Conditions to avoid

Keep away from heat, sparks and flame.

### 10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

### **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

: Not classified Acute toxicity (oral)

Harmful in contact with skin. Acute toxicity (dermal)

Acute toxicity (inhalation) Not classified

Skin corrosion/irritation Causes severe skin burns. Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitization Not classified Not classified Germ cell mutagenicity Carcinogenicity : Not classified Reproductive toxicity Not classified

STOT-single exposure May cause respiratory irritation.

STOT-repeated exposure : Not classified : Not classified Aspiration hazard : No data available Viscosity, kinematic

Potential Adverse human health effects and

symptoms

Absorption of excessive F- can result in acute systemic fluorosis with hypocalcemia, interference with various metabolic functions and organ damage (heart, liver, kidneys).

The most important known symptoms and effects are described in the labelling (see section 2.2)

and/or in section 11.

Symptoms/effects after inhalation : Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough,

shortness of breath, headache, nausea.

### **SECTION 12: Ecological information**

### 12.1. Toxicity

Symptoms/effects

No additional information available

### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

No additional information available

10/4/2022 (Issue date) EN (English US) 6/10

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Waste treatment methods : Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.

Product/Packaging disposal recommendations : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Recycle the material as far as possible.

### **SECTION 14: Transport information**

### 14.1. UN number

DOT NA No : UN3265 UN-No. (TDG) : Not applicable UN-No. (IMDG) : 3265 UN-No. (IATA) : 3265

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Corrosive liquid, acidic, organic, n.o.s.

Proper Shipping Name (TDG) : Not applicable

Proper Shipping Name (IMDG) : CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.

Proper Shipping Name (IATA) : Corrosive liquid, acidic, organic, n.o.s.

### 14.3. Transport hazard class(es)

#### DOT

Transport hazard class(es) (DOT) : 8
Hazard labels (DOT) : 8



**TDG** 

Transport hazard class(es) (TDG) : Not applicable

#### **IMDG**

Transport hazard class(es) (IMDG) : 8
Hazard labels (IMDG) : 8



### IATA

Transport hazard class(es) (IATA) : 8
Hazard labels (IATA) : 8



### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 14.4. Packing group

Packing group (DOT) : III

Packing group (TDG) : Not applicable

Packing group (IMDG) : 111 Packing group (IATA) : 111

### 14.5. Environmental hazards

Other information : No supplementary information available.

### 14.6. Special precautions for user

UN-No.(DOT) UN3265

DOT Special Provisions (49 CFR 172.102) 386 - Notwithstanding the provisions of §177.834(I) of this subchapter, cargo heaters may be

used when weather conditions are such that the freezing of a wetted explosive material is likely. Shipments must be made by private, leased or contract carrier vehicles under exclusive use of the offeror. Cargo heaters must be reverse refrigeration (heat pump) units. Shipments made in accordance with this Special provision are excepted from the requirements of §173.60(b)(4) of

this subchapter.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T7 - 4 178.274(d)(2) Normal...... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154 DOT Packaging Non Bulk (49 CFR 173.xxx) 203 DOT Packaging Bulk (49 CFR 173.xxx) 241 DOT Quantity Limitations Passenger aircraft/rail (49 : 5 L

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

**DOT Vessel Stowage Location** : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

**DOT Vessel Stowage Other** : 40 - Stow "clear of living quarters"

**TDG** 

Emergency Response Guide (ERG) Number : 153

**IMDG** 

Special provision (IMDG) : 223, 274 : 5 L Limited quantities (IMDG) Excepted quantities (IMDG) : E1 : P001, LP01 Packing instructions (IMDG) IBC packing instructions (IMDG) : IBC03 Tank instructions (IMDG) : T7 Tank special provisions (IMDG) : TP1. TP28

: F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE EmS-No. (Fire)

S-B - SPILLAGE SCHEDULE Bravo - CORROSIVE SUBSTANCES EmS-No. (Spillage)

Stowage category (IMDG) Α : Stowage and handling (IMDG) SW2

10/4/2022 (Issue date) EN (English US) 8/10

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Segregation (IMDG) : SGG1, SG36, SG49

Properties and observations (IMDG) : Causes burns to skin, eyes and mucous membranes.

**IATA** 

PCA Excepted quantities (IATA) : E1 PCA Limited quantities (IATA) : Y841 PCA limited quantity max net quantity (IATA) : 1L PCA packing instructions (IATA) : 852 PCA max net quantity (IATA) : 5L CAO packing instructions (IATA) : 856 CAO max net quantity (IATA) 60L Special provision (IATA) : A3, A803 ERG code (IATA) : 8L

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

### **SECTION 15: Regulatory information**

#### 15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

### 15.2. International regulations

#### **CANADA**

### Diphenyldifluorosilane (312-40-3)

Listed on the Canadian NDSL (Non-Domestic Substances List)

#### **EU-Regulations**

### Diphenyldifluorosilane (312-40-3)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

### **National regulations**

No additional information available

### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

### **SECTION 16: Other information**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases		
H312	Harmful in contact with skin	
H314	Causes severe skin burns and eye damage	
H318	Causes serious eye damage	
H335	May cause respiratory irritation	


### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA health hazard : 3 - Materials that, under emergency conditions, can cause serious or permanent injury.

: 1 - Materials that must be preheated before ignition can occur.

: 0 - Material that in themselves are normally stable, even under fire



Hazard Rating

Physical

NFPA fire hazard

NFPA reactivity

: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is Health

given

Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)

: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT

react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Safety Data Sheet (SDS), USA

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.