

# Safety Data Sheet 5681506

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 11/13/2018 Version: 1.0

### **SECTION 1: Identification**

#### 1.1. Identification

Product form : Substance

Substance name : Chloro(dimethyl)phenylsilane

 CAS No
 : 768-33-2

 Product code
 : 5681-5-06

 Formula
 : C8H11CISi

Synonyms : Chlorodimethylphenylsilane / Silane, phenyldimethylchloro- / Benzene, (chlorodimethylsilyl)-

Other means of identification : MFCD00000499

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Laboratory chemicals

Manufacture of substances

Scientific research and development

### 1.3. Details of the supplier of the safety data sheet

SynQuest Laboratories. Inc.

P.O. Box 309

Alachua, FL 32615 - United States of America

T (386) 462-0788 - F (386) 462-7097

info@synquestlabs.com - www.synquestlabs.com

#### 1.4. Emergency telephone number

Emergency number : (844) 523-4086 (3E Company - Account 10069)

# SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

#### **Classification (GHS-US)**

Flam. Liq. 4 H227 - Combustible liquid

Skin Corr. 1A H314 - Causes severe skin burns and eye damage

Eye Dam. 1 H318 - Causes serious eye damage STOT SE 3 H335 - May cause respiratory irritation

Full text of H-phrases: see section 16

# 2.2. Label elements

# **GHS-US** labeling

Hazard pictograms (GHS-US)





GHS05 GHS07

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H227 - Combustible liquid

H314 - Causes severe skin burns and eye damage

H335 - May cause respiratory irritation

Precautionary statements (GHS-US) : P210 - Keep away from heat/sparks/open flames/hot surfaces. No smoking

P260 - Do not breathe fumes, mist, spray, vapors P264 - Wash skin thoroughly after handling

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves/protective clothing/eye protection/face protection P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/ physician

P321 - Specific treatment (see supplemental first aid instructions on this label)

P363 - Wash contaminated clothing before reuse

P370+P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

11/13/2018 EN (English US) SDS ID: 5681506 Page 1

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P403+P235 - Store in a well-ventilated place. Keep cool

P405 - Store locked up

P501 - Dispose of contents/container to an approved waste disposal plant

#### 2.3. Other hazards

No additional information available

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## **SECTION 3: Composition/information on ingredients**

#### 3.1. Substance

Substance type : Mono-constituent

Name	Product identifier	%	Classification (GHS-US)
Chloro(dimethyl)phenylsilane (Main constituent)	(CAS No) 768-33-2	<= 100	Flam. Liq. 4, H227 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335

Full text of H-phrases: see section 16

#### 3.2. Mixture

Not applicable

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

First-aid measures general : In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Move the affected personnel away from the contaminated area.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial

respiration. Get immediate medical advice/attention.

First-aid measures after skin contact : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Get immediate

medical advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid measures after ingestion : Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : The most important known symptoms and effects are described in the labelling (see section

2.2) and/or in section 11.

Symptoms/injuries after inhalation : Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough,

shortness of breath, headache, nausea.

# 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

#### **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

Suitable extinguishing media : Alcohol resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing media appropriate for surrounding fire.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Thermal decomposition generates: Carbon oxides. Hydrogen chloride. Silicon oxides.

Explosion hazard : Risk of explosion if heated under confinement. Use water spray or fog for cooling exposed

containers.

# 5.3. Advice for firefighters

Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection during firefighting : Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".

# SECTION 6: Accidental release measures

# 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate unnecessary personnel. Ensure adequate air ventilation. Do not breathe gas, fumes, vapor or spray.

11/13/2018 EN (English US) SDS ID: 5681506 2/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 6.1.1. For non-emergency personnel

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground

level.

#### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so. Dike for recovery or absorb with appropriate material.

Methods for cleaning up : Take up large spills with pump or vacuum and finish with dry chemical absorbent. Use

explosion-proof equipment. Take up small spills with dry chemical absorbent. Sweep or shovel

spills into appropriate container for disposal. Ventilate area.

Other information : For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

#### 6.4. Reference to other sections

No additional information available

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Ensure good

ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal

protective equipment. Avoid contact with skin and eyes.

Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or

smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Keep container closed when not in use. Moisture sensitive. Keep contents under inert gas.

Incompatible materials : Refer to Section 10 on Incompatible Materials.

Storage area : Store in dry, cool, well-ventilated area.

# SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

No additional information available

#### 8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers

should be available in the immediate vicinity of any potential exposure.

Hand protection : Protective gloves. 29 CFR 1910.138: Hand Protection.

Eye protection : Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory

Protection.

Other information : Safety shoes. 29 CFR 1910.136: Foot Protection.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : No data available
Odor : No data available
Odor threshold : No data available
pH : No data available
Melting point : No data available
Freezing point : No data available
Boiling point : 192 - 193 °C

11/13/2018 EN (English US) SDS ID: 5681506 3/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Flash point : 62 °C

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : No data available **Explosion limits** : No data available No data available Explosive properties Oxidizing properties : No data available : No data available Vapor pressure Relative density : No data available Relative vapor density at 20 °C : No data available Specific gravity / density : 1.017 g/ml Molecular mass : 170.711 g/mol Solubility : No data available : No data available Log Pow : No data available Auto-ignition temperature Decomposition temperature : No data available Viscosity No data available Viscosity, kinematic : No data available

9.2. Other information

Refractive index : 1.5082

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Viscosity, dynamic

No additional information available

### 10.2. Chemical stability

The product is stable at normal handling and storage conditions.

# 10.3. Possibility of hazardous reactions

No additional information available

## 10.4. Conditions to avoid

Keep away from heat, sparks and flame.

## 10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents.

# 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

# **SECTION 11: Toxicological information**

# 11.1. Information on toxicological effects

Acute toxicity : Not classified

Skin corrosion/irritation : Causes severe skin burns and eye damage.

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : May cause respiratory irritation.

Specific target organ toxicity (repeated

exposure)

: Not classified

: No data available

Aspiration hazard : Not classified

11/13/2018 EN (English US) SDS ID: 5681506 4/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/injuries after inhalation

: Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea,

# **SECTION 12: Ecological information**

#### 12.1. **Toxicity**

No additional information available

#### 12.2. Persistence and degradability

No additional information available

#### Bioaccumulative potential

No additional information available

#### 12.4. **Mobility in soil**

No additional information available

#### Other adverse effects

No additional information available

# **SECTION 13: Disposal considerations**

#### Waste treatment methods

Waste treatment methods

: Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.

Waste disposal recommendations

: Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information

: Recycle the material as far as possible.

# **SECTION 14: Transport information**

## **Department of Transportation (DOT)**

In accordance with DOT

Transport document description : UN2987 Chlorosilanes, corrosive, n.o.s., 8, II

UN-No.(DOT) : UN2987

Proper Shipping Name (DOT) Chlorosilanes, corrosive, n.o.s.

Transport hazard class(es) (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

: 206

: None

Hazard labels (DOT) : 8 - Corrosive



Packing group (DOT)

: II - Medium Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx)

DOT Special Provisions (49 CFR 172.102)

: 242 : B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are

not authorized.

T14 - 6 6 mm Prohibited 178.275(g)(3).

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

TP7 - The vapor space must be purged of air by nitrogen or other means.

TP13 - Self-contained breathing apparatus must be provided when this hazardous material is transported by sea.

TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx)

11/13/2018 EN (English US) SDS ID: 5681506 5/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Quantity Limitations Passenger aircraft/rail : Forbidden

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 30 L

CFR 175.75)

DOT Vessel Stowage Location : C - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Other information : No supplementary information available.

**TDG** 

No additional information available

Transport by sea

UN-No. (IMDG) : 2987

Proper Shipping Name (IMDG) : CHLOROSILANES, CORROSIVE, N.O.S.

Class (IMDG) : 8 - Corrosive substances

Packing group (IMDG) : II - substances presenting medium danger

Air transport

UN-No. (IATA) : 2987

Proper Shipping Name (IATA) : Chlorosilanes, corrosive, n.o.s.

Class (IATA) : 8 - Corrosives
Packing group (IATA) : II - Medium Danger

# **SECTION 15: Regulatory information**

#### 15.1. US Federal regulations

#### Chloro(dimethyl)phenylsilane (768-33-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

# 15.2. International regulations

#### CANADA

# Chloro(dimethyl)phenylsilane (768-33-2)

Listed on the Canadian NDSL (Non-Domestic Substances List)

# **EU-Regulations**

No additional information available

## National regulations

# Chloro(dimethyl)phenylsilane (768-33-2)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Japanese ISHL (Industrial Safety and Health Law)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

# 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

# **SECTION 16: Other information**

11/13/2018 EN (English US) SDS ID: 5681506 6/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### Full text of H-phrases:

Eye Dam. 1	Serious eye damage/eye irritation Category 1
Flam. Lig. 4	Flammable liquids Category 4
Skin Corr. 1A	Skin corrosion/irritation Category 1A
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H227	Combustible liquid
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H335	May cause respiratory irritation


NFPA health hazard : 3 - Short exposure could cause serious temporary or

residual injury even though prompt medical attention was

NFPA fire hazard : 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.

0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



HMIS III Rating

NFPA reactivity

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

Flammability : 2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient

temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F

but below 200 F. (Classes II & IIIA)

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT

react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.

11/13/2018 EN (English US) SDS ID: 5681506 7/7