

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations SDS ID: 6164332 Issue date: 1/13/2016 Revision date: 6/1/2023 Version: 1.0

SECTION 1: Identification

1.1. Identification	
Product form Substance name CAS-No. Product code Formula Synonyms Other means of identification	 Substance Triethylsilyl trifluoromethanesulfonate 79271-56-0 6164-3-32 C7H15F3O3SSi Triethylsilyl triflate MFCD00000407
1.2. Recommended use and restrictions on	use
Use of the substance/mixture	: Laboratory chemicals Manufacture of substances Scientific research and development
1.3. Supplier	
SynQuest Laboratories, Inc. Inc. P.O. Box 309 Alachua, FL, Alachua, 32615 United States of America T (386) 462-0788 - F (386) 462-7097 info@synquestlabs.com - www.synquestlabs.com	
1.4. Emergency telephone number	
Emergency number	: (844) 523-4086 (3E Company - Account 10069)
SECTION 2: Hazard(s) identification	
2.1. Classification of the substance or mixt	ıre
GHS US classification	
Flammable liquids Category 4 Skin corrosion/irritation Category 1A Serious eye damage/eye irritation Category 1 Specific target organ toxicity – Single exposure, Cate	H227 Combustible liquid H314 Causes severe skin burns and eye damage H318 Causes serious eye damage egory 3, H335 May cause respiratory irritation

Respiratory tract irritation Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)

Signal word (GHS US) Hazard statements (GHS US)



: Danger

: H227 - Combustible liquid

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

H335 - May cause respiratory irritation

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS US)	: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P260 - Do not breathe fumes, mist, spray, vapors.
	P264 - Wash skin thoroughly after handling
	P271 - Use only outdoors or in a well-ventilated area.
	P280 - Wear protective gloves/protective clothing/eye protection/face protection.
	P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.
	P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
	P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.
	P310 - Immediately call a POISON CENTER or doctor/ physician
	P321 - Specific treatment (see supplemental first aid instructions on this label)
	P363 - Wash contaminated clothing before reuse.
	P370+P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish
	P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
	P403+P235 - Store in a well-ventilated place. Keep cool.
	P405 - Store locked up.
	P501 - Dispose of contents/container to an approved waste disposal plant

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Substance type

: Mono-constituent

Name	Product identifier	%	GHS US classification
Triethylsilyl trifluoromethanesulfonate (Main constituent)	CAS-No.: 79271-56-0		Flam. Liq. 4, H227 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures	
4.1. Description of first aid measures	
First-aid measures general	: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Move the affected personnel away from the contaminated area.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Get immediate medical advice/attention.
First-aid measures after skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Get immediate medical advice/attention.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
First-aid measures after ingestion	 Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get immediate medical advice/attention.
4.2. Most important symptoms and effects ((acute and delayed)
Symptoms/effects	: The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.
Symptoms/effects after inhalation	: Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures	;
5.1. Suitable (and unsuitable) extinguis	shing media
Suitable extinguishing media	: Alcohol resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing media appropriate for surrounding fire.
5.2. Specific hazards arising from the c	chemical
Fire hazard Explosion hazard	 Thermal decomposition generates: Carbon oxides. Hydrogen fluoride. Sulfur oxides. Risk of explosion if heated under confinement. Use water spray or fog for cooling exposed containers. May form flammable/explosive vapor-air mixture.
5.3. Special protective equipment and	precautions for fire-fighters
Firefighting instructions Protection during firefighting	 In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 6: Accidental release measures	5
6.1. Personal precautions, protective equipme	ent and emergency procedures
General measures :	Evacuate unnecessary personnel. Ensure adequate air ventilation. Do not breathe gas, fumes, vapor or spray.
6.1.1. For non-emergency personnel	
Emergency procedures :	Only qualified personnel equipped with suitable protective equipment may intervene.
6.1.2. For emergency responders	
Protective equipment :	Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures :	Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of ignition.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment

: Stop leak if safe to do so. Dike for recovery or absorb with appropriate material.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methods for cleaning up	: Take up large spills with pump or vacuum and finish with dry chemical absorbent. Use explosion- proof equipment. Take up small spills with dry chemical absorbent. Sweep or shovel spills into appropriate container for disposal. Ventilate area.
Other information	: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".
6.4. Reference to other sections	

No additional information available

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Additional hazards when processed Precautions for safe handling Hygiene measures	 Handle empty containers with care because residual vapors are flammable. Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be followed. Use only non-sparking tools. Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, including	g any incompatibilities
Technical measures Storage conditions	 Comply with applicable regulations. Keep container closed when not in use. Keep away from ignition sources. Moisture sensitive. Keep contents under inert gas.
Incompatible materials Storage area	 Refer to Section 10 on Incompatible Materials. Store in dry, cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Triethylsilyl trifluoromethanesulfonate (79271-56-0)		
No additional information available		
8.2. Appropriate engineering controls		
Appropriate engineering controls :	Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.	
8.3. Individual protection measures/Personal	protective equipment	
Hand protection:		
protective gloves. 29 CFR 1910.138: Hand Protection		
Eye protection:		
Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection		
Skin and body protection:		
Wear suitable protective clothing		
Respiratory protection:		
In case of inadequate ventilation wear respiratory prot	ection. 29 CFR 1910.134: Respiratory Protection	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Personal protective equipment symbol(s):



Other information:

Safety shoes. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Dhusiashatata	
Physical state	: Liquid
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
рН	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 85 – 86 °C (@ 12 mm Hg)
Flash point	: 66 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Density	: 1.169 g/ml (@ 20 °C)
Molecular mass	: 264.34 g/mol
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
<u>.</u>	
9.2. Other information	
Refractive index	: 1.389 (@ 20 °C)

SECTION 10: Stability and reactivity	
10.1. Reactivity	
No additional information available	
10.2. Chemical stability	
The product is stable at normal handling and storage conditions.	
10.3. Possibility of hazardous reactions	

No additional information available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.4. Conditions to avoid

Keep away from heat, sparks and flame. Moisture.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

SECTION 11: Toxicological information 11.1. Information on toxicological effects : Not classified Acute toxicity (oral) Not classified Acute toxicity (dermal) ÷ Not classified Acute toxicity (inhalation) : Skin corrosion/irritation Causes severe skin burns. : Serious eye damage/irritation : Causes serious eye damage. Respiratory or skin sensitization : Not classified Germ cell mutagenicity Not classified : Carcinogenicity : Not classified ÷ Reproductive toxicity Not classified STOT-single exposure : May cause respiratory irritation. : Not classified STOT-repeated exposure : Not classified Aspiration hazard : No data available Viscosity, kinematic Symptoms/effects ÷ The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11. Symptoms/effects after inhalation : Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.

SECTION 12: Ecological information

12.1. Toxicity
No additional information available
12.2. Persistence and degradability
No additional information available
12.3. Bioaccumulative potential
No additional information available
12.4. Mobility in soil
No additional information available
12.5. Other adverse effects
No additional information available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations			
SECTION 13: Disposal consideration	S		
13.1. Disposal methods			
Waste treatment methods Product/Packaging disposal recommendations Additional information	 Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber. Dispose of contents/container in accordance with licensed collector's sorting instructions. Recycle the material as far as possible. 		
SECTION 14: Transport information			
14.1. UN number			
DOT NA No UN-No. (TDG) UN-No. (IMDG) UN-No. (IATA)	: UN3265 : UN3265 : 3265 : 3265		
14.2. UN proper shipping name			
Proper Shipping Name (DOT) Proper Shipping Name (TDG) Proper Shipping Name (IMDG) Proper Shipping Name (IATA)	 Corrosive liquid, acidic, organic, n.o.s. 		
14.3. Transport hazard class(es)			
DOT Transport hazard class(es) (DOT) Hazard labels (DOT)	: 8 : 8 CORROSIVE		
TDG Transport hazard class(es) (TDG) Hazard labels (TDG)	: 8 : 8		
IMDG Transport hazard class(es) (IMDG) Hazard labels (IMDG)			
IATA Transport hazard class(es) (IATA) Hazard labels (IATA)	: 8 : 8		

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



	8
14.4. Packing group	
Packing group (DOT) Packing group (TDG) Packing group (IMDG) Packing group (IATA)	: II : II : II : II
14.5. Environmental hazards	
Other information	: No supplementary information available.
14.6. Special precautions for user	
DOT UN-No.(DOT) DOT Special Provisions (49 CFR 172.102)	 UN3265 148 - Except for transportation by aircraft, when transported as a limited quantity or a consumer commodity, the maximum net capacity specified in §173.150(b)(2) of this subchapter for inner packaging may be increased to 5 L (1.3 gallons). B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized. IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. TT1 - 6 178.274(d)(2) Normal
DOT Packaging Exceptions (49 CFR 173.xxx) DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx) DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 154 : 202 : 242 0 : 1 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 30 L
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"
TDG UN-No. (TDG)	: UN3265

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TDG Special Provisions	 16 - 1) The technical name of the most dangerous substance related to the primary class must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(i)(A) of Part 3, Documentation. The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3) of Part 4, Dangerous Goods Safety Marks. 2) subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical: a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S; b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S; c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S; d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S. An example in Canada is the
	"Food and Drugs Act".
Explosive Limit and Limited Quantity Index	: 1L
Excepted quantities (TDG)	: E2
Passenger Carrying Road Vehicle or Passenger	: 1L
Carrying Railway Vehicle Index Emergency Response Guide (ERG) Number	: 153
Energency Response Guide (ERG) Number	. 155
IMDG	
Special provision (IMDG)	: 274
Limited quantities (IMDG)	: 1L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T11
Tank special provisions (IMDG)	: TP2, TP27
EmS-No. (Fire)	: F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage)	: S-B - SPILLAGE SCHEDULE Bravo - CORROSIVE SUBSTANCES
Stowage category (IMDG)	: B
Stowage and handling (IMDG)	: SW2
Segregation (IMDG)	: SGG1, SG36, SG49
Properties and observations (IMDG)	: Causes burns to skin, eyes and mucous membranes.
ΙΑΤΑ	
PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y840
PCA limited quantity max net quantity (IATA)	: 0.5L
PCA packing instructions (IATA)	: 851
PCA max net quantity (IATA)	: 1L
CAO packing instructions (IATA)	: 855
CAO max net quantity (IATA)	: 30L
Special provision (IATA)	: A3, A803
ERG code (IATA)	: 8L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information				
15.1. US Federal regulations				
All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:				
Triethylsilyl trifluoromethanesulfonate	CAS-No. 79271-56-0	100%		

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2. International regulations

CANADA

No additional information available

EU-Regulations

Triethylsilyl trifluoromethanesulfonate (79271-56-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date : 6/1/2023

Full text of H-phrases				
H227	Combustible liquid			
H314	Causes severe skin burns and eye damage			
H318	Causes serious eye damage			
H335	May cause respiratory irritation			
NFPA health hazard		rials that, under emergency conditions, can cause serious or ent injury.		
NFPA fire hazard		ials that must be moderately heated or exposed to relatively		
NFPA reactivity		bient temperatures before ignition can occur. rial that in themselves are normally stable, even under fire is.		
Hazard Rating				
Health	: 3 Seriou given	s Hazard - Major injury likely unless prompt action is taken and medical treatment is		
Flammability	tempera	ate Hazard - Materials which must be moderately heated or exposed to high ambient sures before ignition will occur. Includes liquids having a flash point at or above 100 F v 200 F. (Classes II IIIA)		
Physical	: 0 Minima	al Hazard - Materials that are normally stable, even under fire conditions, and will NOT h water, polymerize, decompose, condense, or self-react. Non-Explosives.		

Safety Data Sheet (SDS), USA

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.