

Safety Data Sheet 6182301

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 01/16/2017 Version: 1.0

SECTION 1: Identification

Identification

Product form : Substance

Substance name Trimethylsilyl 2-(fluorosulfonyl)difluoroacetate

CAS No. 120801-75-4 Product code 6182-3-01 Formula : C5H9F3O4SSi

Synonyms Trimethylsilyl 2,2-difluoro-2-(fluorosulfonyl)acetate

Other means of identification : MFCD02093343

Relevant identified uses of the substance or mixture and uses advised against

: Laboratory chemicals Use of the substance/mixture

Manufacture of substances

Scientific research and development

Details of the supplier of the safety data sheet

SynQuest Laboratories, Inc.

P.O. Box 309

Alachua, FL 32615 - United States of America

T (386) 462-0788 - F (386) 462-7097

info@synquestlabs.com - www.synquestlabs.com

Emergency telephone number

Emergency number : (844) 523-4086 (3E Company - Account 10069)

SECTION 2: Hazard(s) identification

Classification of the substance or mixture

Classification (GHS-US)

Flam. Liq. 3 H226 - Flammable liquid and vapour Acute Tox. 4 (Oral) H302 - Harmful if swallowed Acute Tox. 4 (Dermal) H312 - Harmful in contact with skin

Acute Tox. 4 (Inhalation) H332 - Harmful if inhaled

H314 - Causes severe skin burns and eye damage Skin Corr. 1B

Eye Dam. 1 H318 - Causes serious eye damage STOT SE 3 H335 - May cause respiratory irritation

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)







GHS07

GHS02 GHS05

Signal word (GHS-US) : Danger

: H226 - Flammable liquid and vapor Hazard statements (GHS-US)

H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled

H314 - Causes severe skin burns and eye damage

H335 - May cause respiratory irritation

P210 - Keep away from heat/sparks/open flames/hot surfaces. No smoking Precautionary statements (GHS-US)

P233 - Keep container tightly closed

P240 - Ground/bond container and receiving equipment

P241 - Use explosion-proof electrical/ventilating/lighting equipment

P242 - Use only non-sparking tools

P243 - Take precautionary measures against static discharge

P260 - Do not breathe fumes, mist, spray, vapors P264 - Wash skin thoroughly after handling

P270 - Do not eat, drink or smoke when using this product P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves/protective clothing/eye protection/face protection

SDS ID: 6182301 01/16/2017 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P301+P312 - If swallowed: Call a POISON CENTER or doctor/ physician if you feel unwell

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting

P302+P352 - If on skin: Wash with plenty of soap and water

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/ physician

P321 - Specific treatment (see supplemental first aid instructions on this label)

P330 - Rinse mouth

P362+P364 - Take off contaminated clothing and wash it before reuse

P363 - Wash contaminated clothing before reuse

P370+P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P403+P235 - Store in a well-ventilated place. Keep cool

P405 - Store locked up

P501 - Dispose of contents/container to an approved waste disposal plant

2.3. Other hazards

No additional information available

Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

Substance

Substance type : Mono-constituent

Name	Product identifier	%	Classification (GHS-US)
Trimethylsilyl 2-(fluorosulfonyl)difluoroacetate (Main constituent)	(CAS No) 120801-75-4	<= 100	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335

Full text of H-phrases: see section 16

Mixture

Not applicable

SECTION 4: First aid measures

			4.4
4.1.	Libectintic	n of firet	aid measures

First-aid measures general : In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Move the affected personnel away from the contaminated area.

: Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial First-aid measures after inhalation

respiration. Get immediate medical advice/attention.

First-aid measures after skin contact Wash with plenty of soap and water. Remove contaminated clothing and shoes. In case of skin contact, wearing rubber gloves rub 2.5% calcium gluconate gel continuously into the affected

area for 1.5 hours or until further medical care is available. Get immediate medical

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse First-aid measures after ingestion mouth out with water. Get immediate medical advice/attention.

Most important symptoms and effects, both acute and delayed

Symptoms/injuries The most important known symptoms and effects are described in the labelling (see section

2.2) and/or in section 11.

Symptoms/injuries after inhalation Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough,

shortness of breath, headache, nausea.

Indication of any immediate medical attention and special treatment needed 4.3.

Treat symptomatically. Absorption of excessive F- can result in acute systemic fluorosis with hypocalcemia, interference with various metabolic functions and organ damage (heart, liver, kidneys).

01/16/2017 EN (English US) SDS ID: 6182301 2/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media : Alcohol resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing media appropriate for surrounding fire.

Special hazards arising from the substance or mixture

Fire hazard : Thermal decomposition generates: Carbon oxides. Hydrogen fluoride. Silicon oxides. Sulfur

Explosion hazard Risk of explosion if heated under confinement. Use water spray or fog for cooling exposed

containers. May form flammable/explosive vapor-air mixture.

5.3. Advice for firefighters

: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Firefighting instructions

Wear gas tight chemically protective clothing in combination with self contained breathing Protection during firefighting apparatus. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

: Evacuate unnecessary personnel. Ensure adequate air ventilation. Do not breathe gas, fumes, General measures

6.1.1. For non-emergency personnel

: Only qualified personnel equipped with suitable protective equipment may intervene. **Emergency procedures**

For emergency responders 6.1.2.

: Do not attempt to take action without suitable protective equipment. For further information Protective equipment

refer to section 8: "Exposure controls/personal protection".

Emergency procedures Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground

level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of

ignition.

Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

Methods and material for containment and cleaning up 6.3.

: Stop leak if safe to do so. Dike for recovery or absorb with appropriate material. For containment

Take up large spills with pump or vacuum and finish with dry chemical absorbent. Use Methods for cleaning up

explosion-proof equipment. Take up small spills with dry chemical absorbent. Sweep or shovel

spills into appropriate container for disposal. Ventilate area.

Other information : For disposal of solid materials or residues refer to section 13: "Disposal considerations".

Reference to other sections

No additional information available

SECTION 7: Handling and storage

Precautions for safe handling

Additional hazards when processed

: Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be

followed. Use only non-sparking tools.

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or Hygiene measures

smoke when using this product. Always wash hands after handling the product.

Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions Keep container closed when not in use. Keep away from ignition sources. Moisture sensitive.

Keep contents under inert gas.

Incompatible materials Refer to Section 10 on Incompatible Materials.

Storage area Store in dry, cool, well-ventilated area.

Special rules on packaging : Do not store in glass.

01/16/2017 EN (English US) SDS ID: 6182301 3/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers

should be available in the immediate vicinity of any potential exposure.

Hand protection : Protective gloves. 29 CFR 1910.138: Hand Protection.

Eye protection : Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory

Protection.

Other information : Safety shoes. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : No data available
Odor : No data available
Odor threshold : No data available
pH : No data available
Melting point : No data available
Freezing point : No data available

Boiling point : 55 - 56 °C (@ 22 mm Hg)

Flash point : 26.7 °C

: No data available Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) No data available **Explosion limits** : No data available Explosive properties : No data available : No data available Oxidizing properties : No data available Vapor pressure Relative density No data available Relative vapor density at 20 °C : No data available : 1.27 g/ml (@ 25 °C) Specific gravity / density Molecular mass : 250.27 g/mol Solubility : No data available Log Pow : No data available Auto-ignition temperature : No data available Decomposition temperature : No data available Viscosity No data available Viscosity, kinematic : No data available

9.2. Other information

Refractive index : 1.367 (@ 20 °C)

SECTION 10: Stability and reactivity

10.1. Reactivity

Viscosity, dynamic

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

Contact with acids liberates toxic gas. Contact with water liberates toxic gas.

01/16/2017 EN (English US) SDS ID: 6182301 4/7

: No data available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.4. Conditions to avoid

Keep away from heat, sparks and flame.

10.5. Incompatible materials

Acids. Glass. Strong bases. Strong oxidizing agents. Water.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed. Dermal: Harmful in contact with skin. Inhalation: Harmful if inhaled.

Skin corrosion/irritation : Causes severe skin burns and eye damage.

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : May cause respiratory irritation.

Specific target organ toxicity (repeated

exposure)

: Not classified

Aspiration hazard : Not classified

Potential Adverse human health effects and

symptoms

: Absorption of excessive F- can result in acute systemic fluorosis with hypocalcemia, interference with various metabolic functions and organ damage (heart, liver, kidneys).

Symptoms/injuries after inhalation : Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.

Waste disposal recommendations : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Recycle the material as far as possible.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN2920 Corrosive liquids, flammable, n.o.s., 8, II

UN-No.(DOT) : UN2920

01/16/2017 EN (English US) SDS ID: 6182301 5/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Proper Shipping Name (DOT) : Corrosive liquids, flammable, n.o.s.

Transport hazard class(es) (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Hazard labels (DOT) : 8 - Corrosive 3 - Flammable liquid



Packing group (DOT) : II - Medium Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) : 202 DOT Packaging Bulk (49 CFR 173.xxx) : 243

DOT Symbols : G - Identifies PSN requiring a technical name

DOT Special Provisions (49 CFR 172.102) : B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are

not authorized.

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the

MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : None DOT Quantity Limitations Passenger aircraft/rail : 1 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 30 L

CFR 175.75)

DOT Vessel Stowage Location : C - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel.

DOT Vessel Stowage Other : 25 - Shade from radiant heat,40 - Stow "clear of living quarters"

Other information : No supplementary information available.

TDG

No additional information available

Transport by sea

UN-No. (IMDG) : 2920

Proper Shipping Name (IMDG) : CORROSIVE LIQUID, FLAMMABLE, N.O.S.

Class (IMDG) : 8 - Corrosive substances

Packing group (IMDG) : II - substances presenting medium danger

Air transport

UN-No. (IATA) : 2920

Proper Shipping Name (IATA) : Corrosive liquid, flammable, n.o.s.

Class (IATA) : 8 - Corrosives
Packing group (IATA) : II - Medium Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

Trimethylsilyl 2-(fluorosulfonyl)difluoroacetate	CAS No 120801-75-4	100%
--	--------------------	------

01/16/2017 EN (English US) SDS ID: 6182301 6/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

SECTION 16: Other information

Full text of H-phrases:

ext of 11 philases.	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Flam. Liq. 3	Flammable liquids Category 3
Skin Corr. 1B	Skin corrosion/irritation Category 1B
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H226	Flammable liquid and vapor
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H332	Harmful if inhaled
H335	May cause respiratory irritation

NFPA health hazard

NFPA fire hazard

NFPA reactivity

: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.

given.

: 3 - Liquids and solids that can be ignited under almost all

ambient conditions.

: 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



HMIS III Rating

Flammability

Physical

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB & IC)

: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.

01/16/2017 EN (English US) SDS ID: 6182301 7/7