

Bis(2-furyl)chlorophosphine Safety Data Sheet 6H73501 according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 05/03/2017 Version: 1.0

: Substance		
: Bis(2-furyl)chlorophosphine		
: 181257-35-2		
: 6H73-5-01		
: C8H6ClO2P		
: Di-2-furanylphosphinous chloride : MFCD01630851		
ubstance or mixture and uses advised against		
: Laboratory chemicals Manufacture of substances Scientific research and development		
ety data sheet		
a .com		
: (844) 523-4086 (3E Company - Account 10069)		
on		
or mixture		
er releases flammable gases h burns and eye damage e damage ory irritation		
: GHS02 GHS05 GHS05 GHS07 CHS07 CHS07 CHS07		
: H261 - In contact with water releases flammable gases H314 - Causes severe skin burns and eye damage		
H335 - May cause respiratory irritation		

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	P370+ P402+ P403+ P405 -	P363 - Wash contaminated clothing before reuse P370+P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish P402+P404 - Store in a dry place. Store in a closed container P403+P233 - Store in a well-ventilated place. Keep container tightly closed P405 - Store locked up P501 - Dispose of contents/container to an approved waste disposal plant		
2.3. Other hazards				
Other hazards not contributing to the classification	: Reacts	violently with water.		
2.4. Unknown acute toxicity (G	HS US)			
Not applicable				
SECTION 3: Composition/infe	ormation on ing	redients		
3.1. Substance				
Substance type	: Mono-o	constituent		
Name		Product identifier	%	Classification (GHS-US)
Bis(2-furyl)chlorophosphine (Main constituent)		(CAS No) 181257-35-2	<= 100	Water-react. 2, H261 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335
Full text of H-phrases: see section 16	·			
3.2. Mixture				
Not applicable				
SECTION 4: First aid measur	es			
4.1. Description of first aid mea	Isures			
First-aid measures general		of accident or if you feel unwell, se possible). Move the affected person		
First-aid measures after inhalation		: Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Get immediate medical advice/attention.		
First-aid measures after skin contact : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Get immediat medical advice/attention.			clothing and shoes. Get immediate	
First-aid measures after eye contact		iately flush eyes thoroughly with wat t and easy to do. Continue rinsing. (
First-aid measures after ingestion		T induce vomiting. Never give anyth out with water. Get immediate media		
4.2. Most important symptoms	and effects, both a	cute and delayed		
Symptoms/injuries : The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.			bed in the labelling (see section	
Symptoms/injuries after inhalation		I is destructive to tissue of the muct ass of breath, headache, nausea.	ious membranes a	and upper respiratory tract. Cough,
4.3. Indication of any immediate medical attention and special treatment needed				
Treat symptomatically.				
SECTION 5: Firefighting mea	sures			
5.1. Extinguishing media				
Suitable extinguishing media	: Dry po	wder. Use extinguishing media appr	opriate for surrour	nding fire.
			•	<u> </u>
5.2. Special hazards arising from the substance or mixture Fire hazard : Thermal decomposition generates: Carbon oxides. Hydrogen chloride. Phosphorus oxides.				chloride. Phosphorus oxides
Explosion hazard : Risk of explosion if heated under confinement. Use water spray or fog for cooling exposed containers.			•	
5.3. Advice for firefighters				
Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.			•	
Protection during firefighting : Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".				

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures					
SECTION 6: Accidental release measures					
6.1. Personal precautions, protective equipment and emergency procedures					
General measures	: Evacuate unnecessary personnel. Ensure adequate air ventilation. Do not breathe gas, fumes, vapor or spray.				
6.1.1. For non-emergency personnel					
Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene.				
6.1.2. For emergency responders					
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".				
Emergency procedures	: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level.				
6.2. Environmental precautions					
Avoid release to the environment. Notify authoritie	s if product enters sewers or public waters.				
6.3. Methods and material for containmen	t and cleaning up				
For containment	: Stop leak if safe to do so. Dike for recovery or absorb with appropriate material.				
Methods for cleaning up	: Take up large spills with pump or vacuum and finish with dry chemical absorbent. Use explosion-proof equipment. Take up small spills with dry chemical absorbent. Sweep or shovel spills into appropriate container for disposal. Ventilate area.				
Other information	: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".				
6.4. Reference to other sections					
No additional information available					
SECTION 7: Handling and storage					
7.1. Precautions for safe handling					
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes.				
Hygiene measures	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.				
7.2. Conditions for safe storage, including any incompatibilities					
Technical measures	: Comply with applicable regulations.				
Storage conditions	: Keep container closed when not in use. Air sensitive. Moisture sensitive. Keep contents under inert gas.				
Incompatible materials	: Refer to Section 10 on Incompatible Materials.				
Storage area	: Store in dry, well-ventilated area.				
SECTION 8: Exposure controls/personal protection					
8.1. Control parameters No additional information available					
8.2. Exposure controls					

Appropriate engineering controls	: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
Hand protection	: Protective gloves. 29 CFR 1910.138: Hand Protection.
Eye protection	: Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection.
Other information	: Safety shoes. 29 CFR 1910.136: Foot Protection.
SECTION 9: Physical and cher	nical properties
9.1. Information on basic physics	al and chemical properties

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

according to Federal Register / Vol. 77, No. 58 / Monda	y, March 26, 2012 / Rules and Regulations				
Odor threshold	: No data available				
рН	: No data available				
Melting point	: No data available				
Freezing point	: No data available				
Boiling point	: 100 °C (@ 0.2 mm Hg)				
Flash point	: No data available				
Relative evaporation rate (butyl acetate=1)	: No data available				
Flammability (solid, gas)	: No data available				
Explosion limits	: No data available				
Explosive properties	: No data available				
Oxidizing properties	: No data available				
Vapor pressure	: No data available				
Relative density	: No data available				
Relative vapor density at 20 °C	: No data available				
Specific gravity / density	: 1.287 g/ml (@ 25 °C)				
Molecular mass	: 200.56 g/mol				
Solubility	: No data available				
Log Pow	: No data available				
Auto-ignition temperature	: No data available				
Decomposition temperature	: No data available				
Viscosity	: No data available				
Viscosity, kinematic	: No data available				
Viscosity, dynamic	: No data available				
9.2. Other information					
Refractive index	: 1.593 (@ 20 °C)				
SECTION 10: Stability and reactivity					
10.1. Reactivity					
No additional information available					
	10.2. Chemical stability The product is stable at normal handling and storage conditions				
The product is stable at normal handling and storage conditions.					
10.3. Possibility of hazardous reactions					
No additional information available					
10.4. Conditions to avoid					
Keep away from heat, sparks and flame.					
10.5. Incompatible materials					
Oxidizing agents. Reducing agents.					
10.6. Hazardous decomposition products					
Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.					
SECTION 11: Toxicological information					
11.1. Information on toxicological effects					
Acute toxicity	: Not classified				
Skin correction/irritation	· Causas savara skin hums and ava damaga				

Skin corrosion/irritation	: Causes severe skin burns and eye damage.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause respiratory irritation.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.

SECT	CTION 12: Ecological information	
12.1.	I. Toxicity	
No add	additional information available	
12.2.	2. Persistence and degradability	
No add	additional information available	
12.3.	3. Bioaccumulative potential	
No add	additional information available	
12.4.	4. Mobility in soil	
No add	additional information available	
12.5.	5. Other adverse effects	

No additional information available

SECTION 13: Disposal considerations				
13.1. Waste treatment methods				
Waste treatment methods	: Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.			
Waste disposal recommendations	: Dispose of contents/container in accordance with licensed collector's sorting instructions.			
Additional information	: Recycle the material as far as possible.			

SECTION 14: Transport information

DOT Packaging Non Bulk (49 CFR 173.xxx)

DOT Special Provisions (49 CFR 172.102)

DOT Packaging Bulk (49 CFR 173.xxx)

Department of Transportation (DOT)

In accordance with DOT Transport document description


UN-No.(DOT) Proper Shipping Name (DOT) Transport hazard class(es) (DOT) Hazard labels (DOT)

Packing group (DOT)

DOT Symbols

: UN3129 Water-reactive liquid, corrosive, n.o.s., 4.3, II

- : UN3129
- : Water-reactive liquid, corrosive, n.o.s.
- : 4.3 Class 4.3 Dangerous when wet material 49 CFR 173.124
- : 4.3 Dangerous when wet



- : II Medium Danger
 - : 202
 - : 243
 - : G Identifies PSN requiring a technical name

: IB1 - Authorized IBCs: Metal (31A, 31B and 31N). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

TP7 - The vapor space must be purged of air by nitrogen or other means.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Packaging Exceptions (49 CFR 173.xxx)	: None
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 1L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 5L
DOT Vessel Stowage Location	: E - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length, but is prohibited from carriage on passenger vessels in which the limiting number of passengers is exceeded.
DOT Vessel Stowage Other	: 85 - Under deck stowage must be in mechanically ventilated space
Other information	: No supplementary information available.
TDG	
No additional information available	
Transport by sea	
UN-No. (IMDG)	: 3129
Proper Shipping Name (IMDG)	: WATER-REACTIVE LIQUID, CORROSIVE, N.O.S.
Class (IMDG)	: 4.3 - Substances which, in contact with water, emit flammable gases
Packing group (IMDG)	: II - substances presenting medium danger
Air transport	
UN-No. (IATA)	: 3129
Proper Shipping Name (IATA)	: Water-reactive liquid, corrosive, n.o.s.
Class (IATA)	: 4.3 - Substances which in Contact with Water emit Flammable Gases
Packing group (IATA)	: II - Medium Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

	Bis(2-furyl)chlorophosphine	CAS No 181257-35-2	100%
--	-----------------------------	--------------------	------

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

SECTION 16: Other information

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full tex	t of H-phrases:		
	Eye Dam. 1 Skin Corr. 1B STOT SE 3		Serious eye damage/eye irritation Category 1
			Skin corrosion/irritation Category 1B
			Specific target organ toxicity (single exposure) Category 3
	Water-react. 2		Substances and mixtures which in contact with water emit flammable gases Category 2
	H261		In contact with water releases flammable gases
	H314		Causes severe skin burns and eye damage
	H318		Causes serious eye damage
	H335		May cause respiratory irritation
	health hazard	: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.	
		: 1 - Must be preheated be	
NFPA reactivity : 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.		res or may react with water with 🛛 🗸 🙀 🗸	
NFPA	specific hazard	: W - Unusual reactivity with water. This indicates a potential hazard using water to fight a fire involving this material. When a compound is both water-reactive and an oxidizer, the W/bar symbol should go in this quadrant and the OX warning is placed immediately below the NFPA diamond.	
HMIS I	II Rating		
Health		: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given	
Flamm	ability	: 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)	
Physica	al	: 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.	

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.