

2-(Methylthio)benzylamine

Safety Data Sheet 76661X0

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 09/19/2016 Version: 1.0

SECTION 1: Identification	
1.1. Identification	
Product form	: Substance
Substance name	: 2-(Methylthio)benzylamine
CAS No	: 56004-83-2
Product code	: 7666-1-X0
Formula	: C8H11NS
Synonyms	: [2-(Methylsulfanyl)phenyl]methylamine; 2-(Aminomethyl)phenyl methyl sulfide
Other means of identification	: MFCD00831039
1.2. Relevant identified uses of the	substance or mixture and uses advised against
Use of the substance/mixture	: Laboratory chemicals Manufacture of substances
	Scientific research and development
1.3. Details of the supplier of the sa	afety data sheet
SynQuest Laboratories, Inc. P.O. Box 309 Alachua, FL 32615 - United States of Ameri T (386) 462-0788 - F (386) 462-7097	ica
info@synquestlabs.com - www.synquestlab	<u>os.com</u>
1.4. Emergency telephone number	
Emergency number	: (844) 523-4086 (3E Company - Account 10069)
SECTION 2: Hazard(s) identificat	tion
2.1. Classification of the substance	
Classification (GHS-US)	
Skin Corr. 1B H314 - Causes severe ski	
Skin Corr. 1B H314 - Causes severe ski Eye Dam. 1 H318 - Causes serious ey	ve damage
Skin Corr. 1BH314 - Causes severe skiEye Dam. 1H318 - Causes serious eySTOT SE 3H335 - May cause respirat	ve damage
Skin Corr. 1BH314 - Causes severe skiEye Dam. 1H318 - Causes serious eySTOT SE 3H335 - May cause respirat	ve damage
Skin Corr. 1B H314 - Causes severe ski Eye Dam. 1 H318 - Causes serious ey STOT SE 3 H335 - May cause respirat Full text of H-phrases: see section 16	ve damage
Skin Corr. 1BH314 - Causes severe skiEye Dam. 1H318 - Causes serious eySTOT SE 3H335 - May cause respiratFull text of H-phrases: see section 162.2.Label elements	ve damage
Skin Corr. 1BH314 - Causes severe skiEye Dam. 1H318 - Causes serious eySTOT SE 3H335 - May cause respiratFull text of H-phrases: see section 162.2.Label elements	ve damage
Skin Corr. 1B H314 - Causes severe ski Eye Dam. 1 H318 - Causes serious ey STOT SE 3 H335 - May cause respirat Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US)	re damage itory irritation
Skin Corr. 1B H314 - Causes severe skii Eye Dam. 1 H318 - Causes serious ey STOT SE 3 H335 - May cause respirat Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling	re damage itory irritation

P321 - Specific treatment (see supplemental first aid instructions on this label) P363 - Wash contaminated clothing before reuse

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P405 - Store locked up

P501 - Dispose of contents/container to an approved waste disposal plant

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ccording to Federal Register / Vol. 77, No. 58 / Monday, N	March 26, 2012 / Rules and Regulations		
2.3. Other hazards			
No additional information available			
2.4. Unknown acute toxicity (GHS US)			
Not applicable			
SECTION 3: Composition/information	on ingredients		
3.1. Substance			
Substance type	: Mono-constituent		
Name	Product identifier	%	Classification (GHS-US)
2-(Methylthio)benzylamine (Main constituent)	(CAS No) 56004-83-2	<= 100	Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335
Full text of H-phrases: see section 16			
3.2. Mixture			
Not applicable			
SECTION 4: First aid measures			
4.1. Description of first aid measures			
First-aid measures general	: In case of accident or if you feel un where possible). Move the affected	,	5 (
First-aid measures after inhalation	: Remove person to fresh air and ke respiration. Get immediate medica	•	ing. If not breathing, give artificial
First-aid measures after skin contact	: Wash with plenty of soap and wate medical advice/attention.	r. Remove contaminated	clothing and shoes. Get immediate
First-aid measures after eye contact	: Immediately flush eyes thoroughly present and easy to do. Continue r		
First-aid measures after ingestion	: Do NOT induce vomiting. Never gir mouth out with water. Get immedia		
4.2. Most important symptoms and effects	s, both acute and delayed		
Symptoms/injuries	: The most important known sympto 2.2) and/or in section 11.	ms and effects are descril	bed in the labelling (see section
Symptoms/injuries after inhalation	: Material is destructive to tissue of t shortness of breath, headache, na		and upper respiratory tract. Cough,
4.3. Indication of any immediate medical	attention and special treatment nee	ded	
Treat symptomatically.			
SECTION 5: Firefighting measures			
5.1. Extinguishing media			
	: Alcohol resistant foam. Carbon dio appropriate for surrounding fire.	xide. Dry powder. Water s	spray. Use extinguishing media
5.2. Special hazards arising from the sub-	stance or mixture		
Fire hazard	: Thermal decomposition generates:	Carbon oxides. Nitrogen	oxides. Sulfur oxides.
Explosion hazard	: Risk of explosion if heated under c containers.	onfinement. Use water sp	ray or fog for cooling exposed
5.3. Advice for firefighters			
Firefighting instructions	: In case of fire: Evacuate area. Figh	t fire remotely due to the	risk of explosion.
Protection during firefighting	: Wear gas tight chemically protective apparatus. For further information		
SECTION 6: Accidental release meas	ures		
6.1. Personal precautions, protective equ	ipment and emergency procedures		
General measures	: Evacuate unnecessary personnel. vapor or spray.	Ensure adequate air vent	ilation. Do not breathe gas, fumes,

Emergency procedures

: Only qualified personnel equipped with suitable protective equipment may intervene.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

loorang to rodorar togistor / vol. 11, tto. 00 / monad	,,
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level.
6.2. Environmental precautions	
Avoid release to the environment. Notify author	ities if product enters sewers or public waters.
6.3. Methods and material for containing	nent and cleaning up
For containment	: Stop leak if safe to do so. Dike for recovery or absorb with appropriate material.
Methods for cleaning up	: Take up large spills with pump or vacuum and finish with dry chemical absorbent. Use explosion-proof equipment. Take up small spills with dry chemical absorbent. Sweep or shovel spills into appropriate container for disposal. Ventilate area.
Other information	: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".
6.4. Reference to other sections	
No additional information available	
SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes.
Hygiene measures	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, includ	ling any incompatibilities
Technical measures	: Comply with applicable regulations.
Storage conditions	: Keep container closed when not in use. Air sensitive. Keep contents under inert gas.
Incompatible materials	: Refer to Section 10 on Incompatible Materials.
Storage area	: Store in dry, cool, well-ventilated area.

SECTION 8: Ex	posure controls/	personal	protection
---------------	------------------	----------	------------

8.1. Control parameters

No additional information available

8.2. Exposure controls	
Appropriate engineering controls	: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
Hand protection	: Protective gloves. 29 CFR 1910.138: Hand Protection.
Eye protection	: Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection.
Other information	: Safety shoes. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

	9.1. Information on basic physical and che	emical properties
I	Physical state :	Liquid
(Color :	No data available
(Odor :	No data available
(Odor threshold :	No data available
I	pH :	No data available
I	Melting point :	No data available
I	Freezing point :	No data available
I	Boiling point :	: 139 - 141 °C (@ 15 mm Hg)
I	Flash point :	No data available
I	Relative evaporation rate (butyl acetate=1) :	No data available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Molecular mass	: 153.24 g/mol
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

9.2. Other information

No additional information available

SECTI	ON 10: Stability and reactivity
10.1.	Reactivity
No additi	ional information available
10.2.	Chemical stability
The prod	duct is stable at normal handling and storage conditions.
10.3.	Possibility of hazardous reactions
No additi	ional information available
10.4.	Conditions to avoid
Keep aw	vay from heat, sparks and flame.
10.5.	Incompatible materials
Acids. Ac	cid chlorides. Acid anhydrides. Strong oxidizing agents.
10.6.	Hazardous decomposition products
Under no	ormal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Causes severe skin burns and eye damage.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

-	
SECT	ION 12: Ecological information
12.1.	Toxicity
No addi	itional information available
12.2.	Persistence and degradability
No addi	itional information available
12.3.	Bioaccumulative potential
No addi	itional information available
12.4.	Mobility in soil
No addi	tional information available
12.5.	Other adverse effects
No addi	itional information available

SECTION 13: Disposal considerat	tions
13.1. Waste treatment methods	
Waste treatment methods	: Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.
Waste disposal recommendations	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Recycle the material as far as possible.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT Transport document description

UN-No.(DOT)

Packing group (DOT)

DOT Symbols

Proper Shipping Name (DOT) Transport hazard class(es) (DOT) Hazard labels (DOT)

- : UN2735 Amines, liquid, corrosive, n.o.s., 8, III
- : UN2735
- : Amines, liquid, corrosive, n.o.s.
- : 8 Class 8 Corrosive material 49 CFR 173.136
- : 8 Corrosive



- : III Minor Danger
- DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx)

DOT Special Provisions (49 CFR 172.102)

- : 203 : 241
- : G Identifies PSN requiring a technical name
- : IB3 Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154

DOT Quantity Limitations Passenger aircraft/rail : 5 L (49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75) DOT Vessel Stowage Location

ation : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Vessel Stowage Other	: 52 - Stow "separated from" acids
Other information	: No supplementary information available.
TDG	
No additional information available	
Transport by sea	
UN-No. (IMDG)	: 2735
Proper Shipping Name (IMDG)	: AMINES, LIQUID, CORROSIVE, N.O.S.
Class (IMDG)	: 8 - Corrosive substances
Packing group (IMDG)	: III - substances presenting low danger
Air transport	
UN-No. (IATA)	: 2735
Proper Shipping Name (IATA)	: Amines, liquid, corrosive, n.o.s.
Class (IATA)	: 8 - Corrosives

Packing group (IATA)	: III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

2-(Methylthio)benzylamine	CAS No 56004-83-2	100%

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

SECTION 16: Other information

Full text of H-phrases:

Eye Dam. 1	Serious eye damage/eye irritation Category 1
Skin Corr. 1B	Skin corrosion/irritation Category 1B
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H335	May cause respiratory irritation

NFPA health hazard	 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given. 	1
NFPA fire hazard	: 1 - Must be preheated before ignition can occur.	
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

HMIS III Rating	
Health	: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given
Flammability	 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)
Physical	: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.