

Silver(I) bis(trifluoromethanesulfonyl)imide Safety Data Sheet 8169216 according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 01/26/2021 Version: 1.0

SECTION 1: Identification				
1.1. Identification				
Product form	: Substance			
Substance name	: Silver(I) bis(trifluoromethanesulfonyl)imide			
CAS No	: 189114-61-2			
Product code	: 8169-2-16			
Formula	: C2AgF6NO4S2			
Synonyms	: Silver bis(trifluoromethanesulfonyl)imide			
Other means of identification	: MFCD08457644			
	substance or mixture and uses advised against			
Use of the substance/mixture	: Laboratory chemicals Manufacture of substances Scientific research and development			
1.3. Details of the supplier of the sa	afety data sheet			
SynQuest Laboratories, Inc. P.O. Box 309 Alachua, FL 32615 - United States of Amer T (386) 462-0788 - F (386) 462-7097 info@synquestlabs.com - www.synquestlab				
1.4. Emergency telephone number				
Emergency number	: (844) 523-4086 (3E Company - Account 10069)			
SECTION 2: Hazard(s) identificat	tion			
2.1. Classification of the substance	e or mixture			
Classification (GHS-US)				
Skin Corr. 1BH314 - Causes severEye Dam. 1H318 - Causes seriouSTOT SE 3H335 - May cause resAquatic Acute 3H402 - Harmful to aqu	spiratory irritation uatic life			
Skin Corr. 1BH314 - Causes severEye Dam. 1H318 - Causes severSTOT SE 3H335 - May cause restAquatic Acute 3H402 - Harmful to aquAquatic Chronic 3H412 - Harmful to aqu	us eye damage spiratory irritation uatic life			
Skin Corr. 1BH314 - Causes severEye Dam. 1H318 - Causes severSTOT SE 3H335 - May cause resAquatic Acute 3H402 - Harmful to aquAquatic Chronic 3H412 - Harmful to aquFull text of H-phrases: see section 16	us eye damage spiratory irritation uatic life			
Skin Corr. 1BH314 - Causes sevenEye Dam. 1H318 - Causes sevenSTOT SE 3H335 - May cause resAquatic Acute 3H402 - Harmful to aquAquatic Chronic 3H412 - Harmful to aquFull text of H-phrases: see section 16	us eye damage spiratory irritation uatic life			
Skin Corr. 1BH314 - Causes severEye Dam. 1H318 - Causes severSTOT SE 3H335 - May cause restAquatic Acute 3H402 - Harmful to aquAquatic Chronic 3H412 - Harmful to aquFull text of H-phrases: see section 162.2.Label elements	us eye damage spiratory irritation uatic life uatic life with long lasting effects			
Skin Corr. 1B H314 - Causes sever Eye Dam. 1 H318 - Causes seriou STOT SE 3 H335 - May cause rest Aquatic Acute 3 H402 - Harmful to aquatic Chronic 3 H412 - Harmful to aquatic Chronic 3 H412 - Harmful to aquatic Chronic 3 Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US)	use eye damage spiratory irritation uatic life uatic life with long lasting effects			
Skin Corr. 1B H314 - Causes severed Eye Dam. 1 H318 - Causes seriou STOT SE 3 H335 - May cause rest Aquatic Acute 3 H402 - Harmful to aquad Aquatic Chronic 3 H412 - Harmful to aquad Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US)	us eye damage spiratory irritation uatic life uatic life with long lasting effects : GHS05 GHS05 GHS07 : Danger			
Skin Corr. 1BH314Causes sevenEye Dam. 1H318Causes seriouSTOT SE 3H335May cause resAquatic Acute 3H402Harmful to aquAquatic Chronic 3H412Harmful to aquFull text of H-phrases: see section 162.2.Label elementsGHS-US labelingGHS-US labeling	use eye damage spiratory irritation uatic life uatic life with long lasting effects			
Skin Corr. 1B H314 - Causes severe Eye Dam. 1 H318 - Causes seriou STOT SE 3 H335 - May cause rest Aquatic Acute 3 H402 - Harmful to aquadic Chronic 3 H412 - Harmful to aquadic Chronic 3 H412 - Harmful to aquadic Chronic 3 Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US)	 us eye damage spiratory irritation uatic life uatic life with long lasting effects i i i i i i i i i i i i i i i i i i i			
Skin Corr. 1B H314 - Causes sever Eye Dam. 1 H318 - Causes seriou STOT SE 3 H335 - May cause res Aquatic Acute 3 H402 - Harmful to aqu Aquatic Chronic 3 H412 - Harmful to aqu Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US) Signal word (GHS-US) Hazard statements (GHS-US)	 us eye damage spiratory irritation uatic life uatic life with long lasting effects i i i i i i i i i i i i i i i i i i i			

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- P403+P233 Store in a well-ventilated place. Keep container tightly closed
- P405 Store locked up
- P501 Dispose of contents/container to an approved waste disposal plant

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1.	Substance	
Substa	ance type	

: Mono-constituent

Name		Broduct identifier	%	Classification (GHS-US)
Silver(I) bis(trifluoromethanesulfonyI)imide		Product identifier (CAS No) 189114-61-2	%	Classification (GHS-US) Skin Corr. 1B, H314
(Main constituent)			x = 100	Eye Dam. 1, H318
				STOT SE 3, H335 Aquatic Acute 3, H402
				Aquatic Chronic 3, H412
Full text of H-phrases: see section 16				
3.2. Mixture				
Not applicable				
SECTION 4: First aid measures				
4.1. Description of first aid measures				
First-aid measures general		se of accident or if you feel unwell, a possible). Move the affected perso		
First-aid measures after inhalation		ove person to fresh air and keep co ration. Get immediate medical advic		thing. If not breathing, give artificial
First-aid measures after skin contact		n with plenty of soap and water. Rer cal advice/attention.	nove contaminate	d clothing and shoes. Get immediate
First-aid measures after eye contact		ediately flush eyes thoroughly with vent and easy to do. Continue rinsing		5 minutes. Remove contact lenses, in nedical advice/attention.
First-aid measures after ingestion	: Do N mout	OT induce vomiting. Never give any h out with water. Get immediate me	thing by mouth to dical advice/attent	an unconscious person. Rinse ion.
4.2. Most important symptoms and e	ffects, both	acute and delayed		
Symptoms/injuries		nost important known symptoms ar and/or in section 11.	d effects are desc	ribed in the labelling (see section
Symptoms/injuries after inhalation		rial is destructive to tissue of the muness of breath, headache, nausea.	icuous membrane	s and upper respiratory tract. Cough
4.3. Indication of any immediate med	ical attentio	n and special treatment needed		
Treat symptomatically.				
SECTION 5: Firefighting measures	S			
5.1. Extinguishing media				
Suitable extinguishing media	: Alcoh	nol resistant foam. Carbon dioxide. I	Dry powder. Water	r spray. Use extinguishing media
5 5		priate for surrounding fire.	<i>,</i>	
5.2. Special hazards arising from the	substance	or mixture		
Fire hazard	: Ther	nal decomposition generates: Carb s. Sulfur oxides.	on oxides. Hydrog	en fluoride. Nitrogen oxides. Silver
5.3. Advice for firefighters				
Firefighting instructions	: In ca	se of fire: Evacuate area.		
Protection during firefighting		gas tight chemically protective clot	hing in combinatio	n with self contained breathing
······································	appa	ratus. For further information refer t	o section 8: "Expo	sure controls/personal protection".
SECTION 6: Accidental release m	easures			
6.1. Personal precautions, protective				
General measures	: Evac	uate unnecessary personnel. Ensur	e adequate air ver	ntilation. Do not breathe dust.
6.1.1. For non-emergency personnel				
Emergency procedures	: Only	qualified personnel equipped with s	uitable protective	equipment may intervene.
	,		•	· · · ·

Safety Data Sheet

6.1.2. For eme	rgency responders	
Protective equipme	nt	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
6.2. Environ	nental precautions	
Avoid release to th	e environment. Notify author	ities if product enters sewers or public waters.
6.3. Methods	and material for containm	ent and cleaning up
For containment		: Stop leak if safe to do so.
Methods for cleani	ng up	: Sweep or shovel spills into appropriate container for disposal. Minimize generation of dust.
Other information		: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".
6.4. Referen	e to other sections	
No additional inform	nation available	
SECTION 7: H	andling and storage	
7.1. Precaut	ons for safe handling	
Precautions for saf	e handling	: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe dust, mist, spray. Wear personal protective equipment. Avoid contact with skin and eyes.
Hygiene measures		: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditio	ns for safe storage, includ	ing any incompatibilities
Technical measure	S	: Comply with applicable regulations.
Storage conditions		: Keep container closed when not in use. Hygroscopic. Keep contents under inert gas.
Incompatible mate	ials	: Refer to Section 10 on Incompatible Materials.
01		Others is drawned and the second state of an and the base of the second the second state of the second

Storage area : Store in dry, cool, well-ventilated area. Light sensitive.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls	
Appropriate engineering controls	: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
Hand protection	: Protective gloves. 29 CFR 1910.138: Hand Protection.
Eye protection	: Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection.
Other information	: Safety shoes. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical an	d chemical properties
Physical state	: Solid
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
рН	: No data available
Melting point	: 248 - 249 °C
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Molecular mass	: 388.014 g/mol
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

9.2. Other information

No additional information available

SECT	ION 10: Stability and reactivity				
10.1.	0.1. Reactivity				
No addi	itional information available				
10.2.	Chemical stability				
The pro	duct is stable at normal handling and storage conditions.				
10.3.	Possibility of hazardous reactions				
No addi	tional information available				
10.4.	Conditions to avoid				
Keep av	way from heat, sparks and flame. Moisture.				
10.5.	Incompatible materials				
Strong	oxidizing agents.				
10.6.	Hazardous decomposition products				

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	Not classified	
Skin corrosion/irritation Serious eye damage/irritation Respiratory or skin sensitization Germ cell mutagenicity Carcinogenicity	Causes severe skin burns and eye damage. Causes serious eye damage. Not classified Not classified Not classified	
Reproductive toxicity Specific target organ toxicity (single exposure)	Not classified Not classified May cause respiratory irritation.	
Specific target organ toxicity (repeated exposure)	Not classified	
Aspiration hazard	Not classified	. e.le
Symptoms/injuries after inhalation	Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Courshortness of breath, headache, nausea.	.gn,

SECT	ION 12: Ecological information
12.1.	Toxicity
No add	itional information available
12.2.	Persistence and degradability
No add	itional information available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3.	Bioaccumulative potential		
No addi	tional information available		
12.4.	Mobility in soil		
No addi	tional information available		
12.5.	Other adverse effects		
No addi	tional information available		

SECTION 13: Disposal considerations

Waste treatment methods 13.1.

Waste treatment methods

Waste disposal recommendations Additional information

- : Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.
- : Dispose of contents/container in accordance with licensed collector's sorting instructions. Recycle the material as far as possible.
- **SECTION 14: Transport information**

Department of Transportation (DOT)

In accordance with DOT Transport document description

UN-No.(DOT)

Proper Shipping Name (DOT) Transport hazard class(es) (DOT) Hazard labels (DOT)

: UN1759

: UN1759 Corrosive solids, n.o.s., 8, III

- : Corrosive solids, n.o.s.
- : 8 Class 8 Corrosive material 49 CFR 173.136
- : 8 Corrosive



- Packing group (DOT)
- DOT Packaging Non Bulk (49 CFR 173.xxx)
- DOT Packaging Bulk (49 CFR 173.xxx)
- DOT Symbols
- DOT Special Provisions (49 CFR 172.102)
- : III Minor Danger
- : 213
- : 240
- : G Identifies PSN requiring a technical name

: 128 - Regardless of the provisions of §172.101(c)(12), aluminum smelting by-products and aluminum remelting by-products described under this entry, meeting the definition of Class 8, Packing Group II and III may be classed as a Division 4.3 material and transported under this entry. The presence of a Class 8 hazard must be communicated as required by this Part for subsidiary hazards

IB8 - Authorized IBCs: Metal (11A, 11B, 11N, 21A, 21B, 21N, 31A, 31B and 31N): Rigid plastics (11H1, 11H2, 21H1, 21H2, 31H1 and 31H2); Composite (11HZ1, 11HZ2, 21HZ1, 21HZ2, 31HZ1 and 31HZ2); Fiberboard (11G); Wooden (11C, 11D and 11F); Flexible (13H1, 13H2, 13H3, 13H4, 13H5, 13L1, 13L2, 13L3, 13L4, 13M1 or 13M2). IP3 - Flexible IBCs must be sift-proof and water-resistant or must be fitted with a sift-proof and

water-resistant liner.

T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2)

TP33 - The portable tank instruction assigned for this substance applies for granular and powdered solids and for solids which are filled and discharged at temperatures above their melting point which are cooled and transported as a solid mass. Solid substances transported or offered for transport above their melting point are authorized for transportation in portable tanks conforming to the provisions of portable tank instruction T4 for solid substances of packing group III or T7 for solid substances of packing group II, unless a tank with more stringent requirements for minimum shell thickness, maximum allowable working pressure, pressure-relief devices or bottom outlets are assigned in which case the more stringent tank instruction and special provisions shall apply. Filling limits must be in accordance with portable tank special provision TP3. Solids meeting the definition of an elevated temperature material must be transported in accordance with the applicable requirements of this subchapter.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154 DOT Quantity Limitations Passenger aircraft/rail : 25 kg

(49 CFR 173.27) DOT Quantity Limitations Cargo aircraft only (49 : 100 kg

CFR 175.75)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Other information	: No supplementary information available.
TDG	
No additional information available	
Transport by sea	
UN-No. (IMDG)	: 1759
Proper Shipping Name (IMDG)	: CORROSIVE SOLID, N.O.S.
Class (IMDG)	: 8 - Corrosive substances
Packing group (IMDG)	: III - substances presenting low danger
Air transport	
UN-No. (IATA)	: 1759
Proper Shipping Name (IATA)	: Corrosive solid, n.o.s.
Class (IATA)	: 8 - Corrosives
Packing group (IATA)	: III - Minor Danger

SECTION 15:	Regulatory information
15.1. US Federal	regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

Silver(I) bis(trifiuoromethanesulfonyi)imide CAS No 189114-61-2 100%	Silver(I) bis(trifluoromethanesulfonyl)imide		100%
--	--	--	------

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

No additional information available

EU-Regulations No additional information available

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

SECTION 16: Other information

Full text of H-phrases:

Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Skin Corr. 1B	Skin corrosion/irritation Category 1B
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H335	May cause respiratory irritation
H402	Harmful to aquatic life
H412	Harmful to aquatic life with long lasting effects

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA health hazard	: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.
NFPA fire hazard	: 0 - Materials that will not burn.
NFPA reactivity	: 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.
HMIS III Rating	
Health	: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given
Flammability	: 0 Minimal Hazard - Materials that will not burn
Physical	: 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.