

1-Methyl-1H-pyrazole-5-sulfonyl chloride

Safety Data Sheet 8H625U7

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 04/20/2017 Version: 1.0

SECTION 1: Identification	
1.1. Identification	
Product form	: Substance
Substance name	: 1-Methyl-1H-pyrazole-5-sulfonyl chloride
CAS No	: 1020721-61-2
Product code	: 8H62-5-U7
Formula	: C4H5CIN2O2S
Synonyms	: 5-(Chlorosulfonyl)-1-methyl-1H-pyrazole
Other means of identification	: MFCD09065021
1.2. Relevant identified uses of the subst	tance or mixture and uses advised against
Use of the substance/mixture	: Laboratory chemicals Manufacture of substances Scientific research and development
1.3. Details of the supplier of the safety of	lata sheet
SynQuest Laboratories, Inc. P.O. Box 309 Alachua, FL 32615 - United States of America T (386) 462-0788 - F (386) 462-7097 info@synquestlabs.com - www.synquestlabs.com 1.4. Emergency telephone number	2
Emergency number	: (844) 523-4086 (3E Company - Account 10069)
SECTION 2: Hazard(s) identification	
2.1. Classification of the substance or m	ixture
Classification (GHS-US)Skin Corr. 1BH314 - Causes severe skin burrEye Dam. 1H318 - Causes serious eye damSTOT SE 3H335 - May cause respiratory inFull text of H-phrases: see section 16	nage
2.2. Label elements	
GHS-US labeling	
Hazard pictograms (GHS-US)	: GHS05 GHS07
Signal word (GHS-US)	: Danger
Hazard statements (GHS-US)	: H314 - Causes severe skin burns and eye damage H335 - May cause respiratory irritation
Precautionary statements (GHS-US)	 P260 - Do not breathe fumes, mist, spray, vapors P264 - Wash skin thoroughly after handling P271 - Use only outdoors or in a well-ventilated area P280 - Wear protective gloves/protective clothing/eye protection/face protection P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove cont lenses, if present and easy to do. Continue rinsing P310 - Immediately call a POISON CENTER or doctor/ physician

P321 - Specific treatment (see supplemental first aid instructions on this label) P363 - Wash contaminated clothing before reuse

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P405 - Store locked up P501 - Dispose of contents/container to an approved waste disposal plant

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

 ccording to Federal Register / Vol. 77, No. 58 / Mor 2.3. Other hazards 			
No additional information available			
2.4. Unknown acute toxicity (GHS U	S)		
Not applicable			
SECTION 3: Composition/informa	ation on ingredients		
3.1. Substance			
Substance type	: Mono-constituent		
Name	Product identifier	%	Classification (GHS-US)
1-Methyl-1H-pyrazole-5-sulfonyl chloride (Main constituent)	(CAS No) 1020721-61-2	<= 100	Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335
Full text of H-phrases: see section 16			
3.2. Mixture			
Not applicable			
SECTION 4: First aid measures			
1.1. Description of first aid measure	S		
First-aid measures general	where possible). Move the a	feel unwell, seek medical advic affected personnel away from th	e contaminated area.
First-aid measures after inhalation	respiration. Get immediate r	nedical advice/attention.	hing. If not breathing, give artificial
First-aid measures after skin contact	medical advice/attention.		d clothing and shoes. Get immediate
First-aid measures after eye contact	present and easy to do. Cor	ntinue rinsing. Get immediate m	
First-aid measures after ingestion	mouth out with water. Get ir	ever give anything by mouth to nmediate medical advice/attenti	
4.2. Most important symptoms and e	effects, both acute and delayed		
Symptoms/injuries	: The most important known s 2.2) and/or in section 11.	symptoms and effects are desci	ribed in the labelling (see section
Symptoms/injuries after inhalation	Material is destructive to tiss shortness of breath, headad		s and upper respiratory tract. Cough
4.3. Indication of any immediate me	dical attention and special treatmo	ent needed	
Freat symptomatically.			
SECTION 5: Firefighting measure	es		
5.1. Extinguishing media			
Suitable extinguishing media	: Alcohol resistant foam. Carl appropriate for surrounding	, ,	spray. Use extinguishing media
5.2. Special hazards arising from the	e substance or mixture		
Fire hazard	: Thermal decomposition gen oxides.	erates: Carbon oxides. Hydroge	en chloride. Nitrogen oxides. Sulfur
Explosion hazard	: Risk of explosion if heated u containers.	under confinement. Use water s	pray or fog for cooling exposed
Reactivity	: Reacts with water, generate release highly explosive/flar		osure to water with some metals to
5.3. Advice for firefighters			
Firefighting instructions	: In case of fire: Evacuate are	ea. Fight fire remotely due to the	e risk of explosion.
Protection during firefighting		rotective clothing in combination nation refer to section 8: "Expos	n with self contained breathing sure controls/personal protection".
SECTION 6: Accidental release m			
	e equipment and emergency proc		
General measures	: Evacuate unnecessary pers vapor or spray.	onnel. Ensure adequate air ver	ttilation. Do not breathe gas, fumes,
6.1.1. For non-emergency personnel Emergency procedures	: Only qualified personnel ea	uipped with suitable protective e	equipment may intervene.
	- , , ,		· · · · ·
04/20/2017	EN (English US)	SDS ID: 8H625	5U7 2/7

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.2.	For emergency responders	
Protect	ive equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emerge	ency procedures	: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level.
6.2.	Environmental precautions	
Avoid r	elease to the environment. Notify autho	prities if product enters sewers or public waters.
6.3.	Methods and material for contain	ment and cleaning up
For con	itainment	: Stop leak if safe to do so. Dike for recovery or absorb with appropriate material.
Method	ls for cleaning up	: Take up large spills with pump or vacuum and finish with dry chemical absorbent. Use explosion-proof equipment. Take up small spills with dry chemical absorbent. Sweep or shovel spills into appropriate container for disposal. Ventilate area.
Other ir	nformation	: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".
6.4.	Reference to other sections	
No add	itional information available	
SECT	ION 7: Handling and storage	
7.1.	Precautions for safe handling	
_		
Precaut	tions for safe handling	: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes.
	tions for safe handling e measures	ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal
Hygiene	Ū	 ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Hygiene 7.2.	e measures	 ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Hygiene 7.2. Technic	e measures Conditions for safe storage, inclu	 ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Hygiene 7.2. Technic Storage	e measures Conditions for safe storage, inclu cal measures	 ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. ding any incompatibilities Comply with applicable regulations.

SECTION 8: Exposure controls/personal protection

8.1. **Control parameters**

-

No additional information available

	8.2. Exposure controls	
	Appropriate engineering controls	: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
I	Hand protection	: Protective gloves. 29 CFR 1910.138: Hand Protection.
l	Eye protection	: Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.
;	Skin and body protection	: Wear suitable protective clothing.
I	Respiratory protection	: In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection.
(Other information	: Safety shoes. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and	chemical properties
Physical state	: Liquid
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
рН	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Molecular mass	: 180.61 g/mol
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with water, generates gases or heat. Reacts on exposure to water with some metals to release highly explosive/flammable hydrogen gas.

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Keep away from heat, sparks and flame. Moisture.

10.5. Incompatible materials

Alcohols. Oxidizing agents. Strong bases. Water.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Causes severe skin burns and eye damage.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECT	ION 12: Ecological information
12.1.	Toxicity
No addi	tional information available
12.2.	Persistence and degradability
No addi	tional information available
12.3.	Bioaccumulative potential
No addi	tional information available
12.4.	Mobility in soil
No addi	tional information available
12.5.	Other adverse effects
No add	tional information available

SECTION 13: Disposal considerations		
13.1. Waste treatment methods		
Waste treatment methods : Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.		
Waste disposal recommendations	: Dispose of contents/container in accordance with licensed collector's sorting instructions.	
Additional information	: Recycle the material as far as possible.	

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT Transport document description

UN-No.(DOT)

Packing group (DOT)

DOT Symbols

Proper Shipping Name (DOT) Transport hazard class(es) (DOT) Hazard labels (DOT)

- : UN3265 Corrosive liquid, acidic, organic, n.o.s., 8, III
- : UN3265
- : Corrosive liquid, acidic, organic, n.o.s.
- : 8 Class 8 Corrosive material 49 CFR 173.136
- : 8 Corrosive



- : III Minor Danger
- DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx)

DOT Special Provisions (49 CFR 172.102)

- : 203 : 241
- : G Identifies PSN requiring a technical name
- : IB3 Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T7 - 4 178.274(d)(2) Normal...... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154

DOT Quantity Limitations Passenger aircraft/rail : 5 L (49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75) DOT Vessel Stowage Location

ion : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"
Other information	: No supplementary information available.
TDG	
No additional information available	
Transport by sea	
UN-No. (IMDG)	: 3265
Proper Shipping Name (IMDG)	: CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.
Class (IMDG)	: 8 - Corrosive substances
Packing group (IMDG)	: III - substances presenting low danger
Air transport	
UN-No. (IATA)	: 3265
Proper Shipping Name (IATA)	: Corrosive liquid, acidic, organic, n.o.s.
Class (IATA)	: 8 - Corrosives
Packing group (IATA)	: III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

1-Methyl-1H-pyrazole-5-sulfonyl chloride	CAS No 1020721-61-2	100%

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

SECTION 16: Other information

Full text of H-phrases:

Eye Dam. 1	Serious eye damage/eye irritation Category 1
Skin Corr. 1B	Skin corrosion/irritation Category 1B
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H335	May cause respiratory irritation

NFPA health hazard	: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.	0
NFPA fire hazard	: 0 - Materials that will not burn.	
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

HMIS III Rating	
Health	: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given
Flammability	: 0 Minimal Hazard - Materials that will not burn
Physical	: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.