

Safety Data Sheet 911290D

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 12/09/2019 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Substance

Substance name : n-Propylmagnesium bromide, 1M solution in THF

Product code : 9112-9-0D

Synonyms : Magnesium, bromopropyl-

Other means of identification : MFCD00058928

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Laboratory chemicals

Manufacture of substances

Scientific research and development

1.3. Details of the supplier of the safety data sheet

SynQuest Laboratories, Inc.

P.O. Box 309

Alachua, FL 32615 - United States of America

T (386) 462-0788 - F (386) 462-7097

info@synquestlabs.com - www.synquestlabs.com

1.4. Emergency telephone number

Emergency number : (844) 523-4086 (3E Company - Account 10069)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Lig. 2 H225 - Highly flammable liquid and vapour

Water-react. 1 H260 - In contact with water releases flammable gases which may ignite spontaneously

Acute Tox. 4 (Oral) H302 - Harmful if swallowed Acute Tox. 4 (Inhalation) H332 - Harmful if inhaled

Skin Corr. 1A H314 - Causes severe skin burns and eye damage

Eye Dam. 1 H318 - Causes serious eye damage
STOT SE 3 H336 - May cause drowsiness or dizziness
STOT SE 3 H335 - May cause respiratory irritation
STOT SE 1 H370 - Causes damage to organs

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)







GHS02

HS02

GHS05

GHS07

GHS08

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H225 - Highly flammable liquid and vapor

H260 - In contact with water releases flammable gases which may ignite spontaneously

H302+H332 - Harmful if swallowed or if inhaled H314 - Causes severe skin burns and eye damage H335 - May cause respiratory irritation

H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H370 - Causes damage to organs

Precautionary statements (GHS-US) : P210 - Keep away from heat/sparks/open flames/hot surfaces. No smoking

P223 - Do not allow contact with water

P231+P232 - Handle under inert gas. Protect from moisture

P233 - Keep container tightly closed

P240 - Ground/bond container and receiving equipment

P241 - Use explosion-proof electrical/ventilating/lighting equipment

P242 - Use only non-sparking tools

P243 - Take precautionary measures against static discharge

P260 - Do not breathe fumes, mist, spray, vapors

05/13/2020 EN (English US) SDS ID: 911290D Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P264 - Wash skin thoroughly after handling

P270 - Do not eat, drink or smoke when using this product

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301+P312 - If swallowed: Call a POISON CENTER or doctor/ physician if you feel unwell

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing P307+P311 - If exposed: Call a poison center/doctor

P310 - Immediately call a POISON CENTER or doctor/ physician

P321 - Specific treatment (see supplemental first aid instructions on this label)

P330 - Rinse mouth

P335+P334 - Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages

P363 - Wash contaminated clothing before reuse

P370+P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

P402+P404 - Store in a dry place. Store in a closed container

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P403+P235 - Store in a well-ventilated place. Keep cool

P405 - Store locked up

P501 - Dispose of contents/container to an approved waste disposal plant

2.3. Other hazards

Other hazards not contributing to the classification

: Reacts violently with water.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Substance type : Mono-constituent

Name	Product identifier	%	Classification (GHS-US)
n-Propylmagnesium bromide, 1M solution in THF (Main constituent)		<= 100	Flam. Liq. 2, H225 Water-react. 1, H260 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H336 STOT SE 3, H335 STOT SE 1, H370

Full text of H-phrases: see section 16

3.2. Mixture

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Move the affected personnel away from the contaminated area.

First-aid measures after inhalation

: Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Get immediate medical advice/attention.

First-aid measures after skin contact

: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Get immediate medical advice/attention.

First-aid measures after eye contact

: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid measures after ingestion

: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries

: The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.

Symptoms/injuries after inhalation

: Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.

05/13/2020 EN (English US) SDS ID: 911290D 2/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media : Dry powder. Use extinguishing media appropriate for surrounding fire.

Special hazards arising from the substance or mixture

Fire hazard : Thermal decomposition generates: Carbon oxides. Hydrogen bromide. Magnesium oxide.

Explosion hazard Risk of explosion if heated under confinement. Use water spray or fog for cooling exposed

containers. May form flammable/explosive vapor-air mixture.

Advice for firefighters

Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

Wear gas tight chemically protective clothing in combination with self contained breathing Protection during firefighting

apparatus. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

General measures : Evacuate unnecessary personnel. Ensure adequate air ventilation. Do not breathe gas, fumes,

vapor or spray.

6.1.1. For non-emergency personnel

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground **Emergency procedures**

level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of ignition.

6.2. **Environmental precautions**

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so. Dike for recovery or absorb with appropriate material.

: Take up large spills with pump or vacuum and finish with dry chemical absorbent. Use Methods for cleaning up

explosion-proof equipment. Take up small spills with dry chemical absorbent. Sweep or shovel spills into appropriate container for disposal. Ventilate area.

For disposal of solid materials or residues refer to section 13: "Disposal considerations". Other information

Reference to other sections

No additional information available

SECTION 7: Handling and storage

Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal

protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be

followed. Use only non-sparking tools.

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or Hygiene measures smoke when using this product. Always wash hands after handling the product.

Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Keep container closed when not in use. Keep away from ignition sources. Air sensitive. Storage conditions

Moisture sensitive. Keep contents under inert gas.

Refer to Section 10 on Incompatible Materials. Incompatible materials

Prohibitions on mixed storage Do not store with: Water.

Storage area : Store in dry, well-ventilated area.

05/13/2020 EN (English US) SDS ID: 911290D 3/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers

should be available in the immediate vicinity of any potential exposure.

Hand protection : Protective gloves. 29 CFR 1910.138: Hand Protection.

Eye protection : Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory

Protection.

Other information : Safety shoes. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : No data available
Odor : No data available
Odor threshold : No data available
pH : No data available
Melting point : No data available
Freezing point : No data available
Boiling point : No data available

Flash point : -15 °C

Relative evaporation rate (butyl acetate=1) No data available Flammability (solid, gas) : No data available : No data available **Explosion limits** Explosive properties : No data available : No data available Oxidizing properties : No data available Vapor pressure Relative density No data available Relative vapor density at 20 °C : No data available 147.297 g/mol Molecular mass Solubility : No data available Log Pow : No data available Auto-ignition temperature No data available Decomposition temperature : No data available : No data available Viscosity : No data available Viscosity, kinematic Viscosity, dynamic : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

Reacts violently with water.

05/13/2020 EN (English US) SDS ID: 911290D 4/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.4. Conditions to avoid

Keep away from heat, sparks and flame. Moisture.

10.5. Incompatible materials

Acids. Alcohols. Strong oxidizing agents. Water.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed. Inhalation: Harmful if inhaled.

n-Propylmagnesium bromide, 1M solution in THF	
ATE US (oral)	500.000 mg/kg body weight
ATE US (gases)	4500.000 ppmV/4h
ATE US (vapors)	11.000 mg/l/4h
ATE US (dust, mist)	1.500 mg/l/4h

Skin corrosion/irritation : Causes severe skin burns and eye damage.

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness. May cause respiratory irritation. Causes damage to

organs.

Specific target organ toxicity (repeated

exposure)

: Not classified

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough,

shortness of breath, headache, nausea.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.

Waste disposal recommendations : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Recycle the material as far as possible.

05/13/2020 EN (English US) SDS ID: 911290D 5/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN3399 Organometallic substance, liquid, water-reactive, flammable, 4.3, I

UN-No.(DOT) : UN3399

Proper Shipping Name (DOT) : Organometallic substance, liquid, water-reactive, flammable Transport hazard class(es) (DOT) : 4.3 - Class 4.3 - Dangerous when wet material 49 CFR 173.124

Hazard labels (DOT) 4.3 - Dangerous when wet

3 - Flammable liquid



Packing group (DOT) : I - Great Danger Marine pollutant Yes (IMDG only)



DOT Packaging Non Bulk (49 CFR 173.xxx) : 201

DOT Packaging Bulk (49 CFR 173.xxx) : 244

DOT Symbols

DOT Special Provisions (49 CFR 172.102)

: G - Identifies PSN requiring a technical name

: T13 - 6 6 mm Normal..... Prohibited

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C

(59 F) and 50 C (122 F), respectively.

TP7 - The vapor space must be purged of air by nitrogen or other means.

TP36 - For material assigned this portable tank special provision, portable tanks used to transport such material may be equipped with fusible elements in the vapor space of the

portable

DOT Packaging Exceptions (49 CFR 173.xxx) DOT Quantity Limitations Passenger aircraft/rail : Forbidden

(49 CFR 173.27)

: None

DOT Quantity Limitations Cargo aircraft only (49 : 1 L

CFR 175.75)

DOT Vessel Stowage Location

: D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger

vessels in which the limiting number of passengers is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters",52 - Stow "separated from" acids

Other information : No supplementary information available.

No additional information available

Transport by sea

UN-No. (IMDG)

Proper Shipping Name (IMDG) ORGANOMETALLIC SUBSTANCE, LIQUID, WATER-REACTIVE, FLAMMABLE

Class (IMDG) : 4.3 - Substances which, in contact with water, emit flammable gases

Packing group (IMDG) : I - substances presenting high danger

05/13/2020 EN (English US) SDS ID: 911290D 6/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Air transport

UN-No. (IATA) : 3399

Proper Shipping Name (IATA) : Organometallic substance, liquid, water-reactive, flammable

Class (IATA) : 4.3 - Substances which in Contact with Water emit Flammable Gases

Packing group (IATA) : I - Great Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

n-Propylmagnesium bromide, 1M solution in THF	CAS No	100%
---	--------	------

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

n-Propylmagnesium bromide, 1M solution in THF

Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on the TCSI (Taiwan Chemical Substance Inventory)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

SECTION 16: Other information

Full text of H-phrases:

Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4	
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4	
Eye Dam. 1	Serious eye damage/eye irritation Category 1	
Flam. Liq. 2	Flammable liquids Category 2	
Skin Corr. 1A	Skin corrosion/irritation Category 1A	
STOT SE 1	Specific target organ toxicity (single exposure) Category 1	
STOT SE 3	Specific target organ toxicity (single exposure) Category 3	
STOT SE 3	Specific target organ toxicity (single exposure) Category 3	
Water-react. 1	Substances and mixtures which in contact with water emit flammable gases Category 1	
H225	Highly flammable liquid and vapor	
H260	In contact with water releases flammable gases which may ignite spontaneously	
H302	Harmful if swallowed	
H314	Causes severe skin burns and eye damage	
H318	Causes serious eye damage	
H332	Harmful if inhaled	
H335	May cause respiratory irritation	
H336	May cause drowsiness or dizziness	
H370	Causes damage to organs	

05/13/2020 EN (English US) SDS ID: 911290D 7/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA health hazard	: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.
NFPA fire hazard	: 3 - Liquids and solids that can be ignited under almost all ambient conditions.
NFPA reactivity	: 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.
HMIS III Rating	

: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is Health

given

Flammability : 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above

100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB & IC)

Physical : 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo

hazardous polymerization in the absence of inhibitors.

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.

05/13/2020 SDS ID: 911290D 8/8 EN (English US)