

Phosphorus pentafluoride Safety Data Sheet M015202 according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 04/20/2017 Version: 1.0

SECTION 1: Identification	
1.1. Identification	
Product form	: Substance
Substance name	: Phosphorus pentafluoride
CAS No	: 7647-19-0
Product code	: M015-2-02
Formula	: F5P
Synonyms	: Phosphorus(V) fluoride
	: MFCD00040326
1.2. Relevant identified uses of the substa	ance or mixture and uses advised against
Use of the substance/mixture	: Laboratory chemicals Manufacture of substances Scientific research and development
1.3. Details of the supplier of the safety da	ata sheet
SynQuest Laboratories, Inc. P.O. Box 309 Alachua, FL 32615 - United States of America T (386) 462-0788 - F (386) 462-7097 info@synquestlabs.com	
1.4. Emergency telephone number	
Emergency number	: (844) 523-4086 (3E Company - Account 10069)
SECTION 2: Hazard(s) identification	
2.1. Classification of the substance or mix	xture
Classification (GHS-US)	
Acute Tox. 3 (Oral)H301 - Toxic if swalloAcute Tox. 3 (Dermal)H311 - Toxic in contaAcute Tox. 3 (Inhalation)H331 - Toxic if inhale	ict with skin d e skin burns and eye damage us eye damage
2.2. Label elements	
GHS-US labeling	
Hazard pictograms (GHS-US)	: GHS04 GHS05 GHS06 GHS07
Signal word (GHS-US)	: Danger
Hazard statements (GHS-US)	 H280 - Contains gas under pressure; may explode if heated H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled H314 - Causes severe skin burns and eye damage H335 - May cause respiratory irritation H380 - May displace oxygen and cause rapid suffocation
Precautionary statements (GHS-US)	 P260 - Do not breathe fumes, gas, mist, spray, vapors P264 - Wash skin thoroughly after handling P270 - Do not eat, drink or smoke when using this product P271 - Use only outdoors or in a well-ventilated area P280 - Wear protective gloves/protective clothing/eye protection/face protection P301+P310 - If swallowed: Immediately call a poison center/doctor/ P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting P302+P352 - If on skin: Wash with plenty of soap and water P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

		skin with water/shower P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P310 - Immediately call a POISON CENTER or doctor/ physician P311 - Call a POISON CENTER or doctor/physician P321 - Specific treatment (see supplemental first aid instructions on this label) P330 - Rinse mouth P361 - Take off immediately all contaminated clothing P363 - Wash contaminated clothing before reuse P403+P233 - Store in a well-ventilated place. Keep container tightly closed P405 - Store locked up P410+P403 - Protect from sunlight. Store in a well-ventilated place P501 - Dispose of contents/container to an approved waste disposal plant
2.3.	Other hazards	

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance Substance type

: Mono-constituent

Name	Product identifier	%	Classification (GHS-US)
Phosphorus pentafluoride (Main constituent)	(CAS No) 7647-19-0	<= 100	Simple Asphy, H380 Liquefied gas, H280 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335

Full text of H-phrases: see section 16

3.2. Mixture	
Not applicable	
SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general	: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Move the affected personnel away from the contaminated area.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Get immediate medical advice/attention.
First-aid measures after skin contact	: Thaw frosted parts with lukewarm water. Do no rub affected area. Remove contaminated clothing and shoes. In case of skin contact, wearing rubber gloves rub 2.5% calcium gluconate gel continuously into the affected area for 1.5 hours or until further medical care is available. Get immediate medical advice/attention.
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention. Immediately flush eyes thoroughly with water for at least 15 minutes.
First-aid measures after ingestion	: Due to its physical form, exposure to this chemical is not likely. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get immediate medical advice/attention.
4.2. Most important symptoms and effects	s, both acute and delayed
Symptoms/injuries	: The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.
Symptoms/injuries after inhalation	: May cause drowsiness or dizziness. Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.
Symptoms/injuries after skin contact	: Contact with the liquid the may cause cold burns/frostbite.
Symptoms/injuries after eye contact	: Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to frostbite from rapid liquid evaporation.
4.0 Indiantian of any burned lists and lists	

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Absorption of excessive F- can result in acute systemic fluorosis with hypocalcemia, interference with various metabolic functions and organ damage (heart, liver, kidneys).

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media	: Dry powder. Use extinguishing media appropriate for surrounding fire.
5.2. Special hazards arising from the sul	bstance or mixture
Fire hazard	: Thermal decomposition generates: Hydrogen fluoride. Phosphorus oxides.
Explosion hazard	: Contains gas under pressure; may explode if heated. Use water spray or fog for cooling exposed containers.
5.3. Advice for firefighters	
Firefighting instructions	: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.
Protection during firefighting	: Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".
SECTION 6: Accidental release meas	sures
6.1. Personal precautions, protective eq	uipment and emergency procedures
General measures	: Evacuate unnecessary personnel. Ensure adequate air ventilation. May cause suffocation by reducing oxygen available for breathing. Do not breathe gas, fumes, vapor or spray.
6.1.1. For non-emergency personnel	
Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level.
6.2. Environmental precautions	
Avoid release to the environment. Notify authorit	ies if product enters sewers or public waters.
6.3. Methods and material for containme	ent and cleaning up
For containment	: Stop leak if safe to do so.
Methods for cleaning up	: Ventilate area.
Other information	: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".
6.4. Reference to other sections	
No additional information available	
SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Additional hazards when processed	: Pressurized container: Do not pierce or burn, even after use. Close valve after each use and when empty.
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, gas, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes.
Safe handling of the gas receptacle	: Securely chain cylinders when in use and protect against physical damage.
Hygiene measures	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, including	ng any incompatibilities
Technical measures	: Comply with applicable regulations.
Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep container closed when not in use. Moisture sensitive.
Incompatible materials	: Refer to Section 10 on Incompatible Materials.
Storage area	: Store in dry, cool, well-ventilated area.
SECTION 8: Exposure controls/pers	onal protoction

SECTION 8: Exposure controls/personal protection

8.1. **Control parameters**

No additional information available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2.	Exposure controls		
Approp	riate engineering controls	:	Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Systems under pressure should be regularily checked for leakage. Oxygen detectors should be used when asphyxiating gases may be released. Gas detectors should be used when toxic gases may be released.
Hand p	rotection	:	Protective gloves. 29 CFR 1910.138: Hand Protection.
Eye pro	otection	:	Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.
Skin ar	nd body protection	:	Wear suitable protective clothing.
Respira	atory protection	:	In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection.
Therma	al hazard protection	:	Cold insulating gloves.
Other i	nformation	:	Safety shoes. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and cl	ne	mical properties
Physical state	:	Gas
Color	:	No data available
Odor	:	No data available
Odor threshold	:	No data available
рН	:	No data available
Melting point	:	-91.6 °C
Freezing point	:	No data available
Boiling point	:	-84.8 °C
Flash point	:	No data available
Relative evaporation rate (butyl acetate=1)	:	No data available
Flammability (solid, gas)	:	No data available
Explosion limits	:	No data available
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Vapor pressure	:	415 psia (@ 21 °C)
Relative density	:	No data available
Relative vapor density at 20 °C	:	No data available
Molecular mass	:	125.97 g/mol
Solubility	:	No data available
Log Pow	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	No data available
Viscosity, kinematic	:	No data available
Viscosity, dynamic	:	No data available

Color	: No data available		
Odor	: No data available		
Odor threshold	: No data available		
рН	: No data available		
Melting point	: -91.6 °C		
Freezing point	: No data available		
Boiling point	: -84.8 °C		
Flash point	: No data available		
Relative evaporation rate (butyl acetate=1)	: No data available		
Flammability (solid, gas)	: No data available		
Explosion limits	: No data available		
Explosive properties	: No data available		
Oxidizing properties	: No data available		
Vapor pressure	: 415 psia (@ 21 °C)		
Relative density	: No data available		
Relative vapor density at 20 °C	: No data available		
Molecular mass	: 125.97 g/mol		
Solubility	: No data available		
Log Pow	: No data available		
Auto-ignition temperature	: No data available		
Decomposition temperature	: No data available		
Viscosity	: No data available		
Viscosity, kinematic	: No data available		
Viscosity, dynamic	: No data available		
9.2. Other information			
No additional information available			
SECTION 10: Stability and reactivity			
10.1. Reactivity			
No additional information available	No additional information available		
10.2. Chemical stability			
The product is stable at pormal handling and storage conditions			

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

Contact with acids liberates toxic gas. Contact with water liberates toxic gas.

10.4. **Conditions to avoid**

Protect from sunlight. Do not expose to temperatures exceeding 50 °C Keep away from heat, sparks and flame.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.5. Incompatible materials

Acids. Strong bases. Strong oxidizing agents. Water.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

: Oral: Toxic if swallowed. Dermal: Toxic in contact with skin. Inhalation: Toxic if inhaled.

100.000 mg/kg body weight
300.000 mg/kg body weight
700.000 ppmV/4h
3.000 mg/l/4h
0.500 mg/l/4h
: Causes severe skin burns and eye damage.
: Causes serious eye damage.
: Not classified
: May cause respiratory irritation.
: Not classified
: Not classified
: Absorption of excessive F- can result in acute systemic fluorosis with hypocalcemia, interference with various metabolic functions and organ damage (heart, liver, kidneys).
: May cause drowsiness or dizziness. Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.
: Contact with the liquid the may cause cold burns/frostbite.
: Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to frostbite from rapid liquid evaporation.
-

SECTION 12: Ecological information
12.1. Toxicity
No additional information available
12.2. Persistence and degradability
No additional information available
12.3. Bioaccumulative potential
No additional information available
12.4. Mobility in soil
No additional information available
12.5. Other adverse effects
No additional information available

SECTION 13: Disposal consideration	ons
13.1. Waste treatment methods	
Waste treatment methods	: Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.
Waste disposal recommendations	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Recycle the material as far as possible.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

(see 173.116(a) or 173.133(a) of this subchapter), and must be described as an inhalatic hazard under the provisions of this subchapter. B9 - Bottom outlets are not authorized. B14 - Each bulk packaging, except a tank car or a multi-unit-tank car tank, must be insult with an insultating material as that the overall thermal conductance at 15.5 C (60 F) is no than 1.5333 kilojoules per hour per square meter per degree Celsius (0.075 Btu per hour square foot per degree Fahrenheit) temperature differential. Insulating materials so that the overall thermal conductance at 15.5 C (60 F) is no than 1.5333 kilojoules per hour per square meter per degree Celsius (0.075 Btu per hour square foot per degree Fahrenheit) temperature differential. Insulating materials must no promote corrosion to steel when wet.DOT Packaging Exceptions (49 CFR 173.xxx): NoneDOT Quantity Limitations Passenger aircraft/rail: Forbidden CFR 175.75)DOT Quantity Limitations Cargo aircraft only (49 cFR 175.75): D - The material must be stowed "on deck only" on a cargo vessel and on a passenger v carrying a number of passengers limited to not more than the larger of 25 passengers or passenger per each 3 m of overall vessel length, but the material is prohibited on passen vessels in which the limiting number of passengers is exceeded.DOT Vessel Stowage Other: 40 - Stow "clear of living quarters"ToG No additional information available: No supplementary information available.TDG Proper Shipping Name (IMDG): 2 198Proper Shipping Name (IMDG): 2 198Proper Shipping Name (IMDG): 2 198Proper Shipping Name (IATA): 2 198Proper Shipping Name (IATA): 2 198Proper Shipping Name (IATA): 2 198	Department of Transportation (DOT) In accordance with DOT	
Proper Shipping Name (DOT) : Phosphorus pentafluoride Transport hazard class(es) (DOT) : 2.3 - Poisonous gas 49 CFR 173.115 Hazard labels (DOT) : 2.3 - Poison gas Bord Packaging Non Bulk (49 CFR 173.xxx) : 302.304 DOT Packaging Buk (49 CFR 173.xxx) : 302.304 DOT Special Provisions (49 CFR 173.xxx) : 314.315 DOT Special Provisions (49 CFR 173.xxx) : 314.315 DOT Packaging Exceptions (49 CFR 173.xxx) : None DOT Quantity Limitations Passenger aircraftvall : Forbidden CfR 173.27) : Forbidden OT Vassel Stowage Location : Dor The material must be slowed 'on deck only' on a cargo vessel and on a passenger vessel's an or exceed tank there insult insultating materials prohibited on passenger or passengers initied to not more than the larger of 22 passengers or passenger in each 3 n of overall vessel length, but the material is prohibited on passenger vessel's an or overall vessel and on a passenger or passenger in each 3 n of overall vessel length, but the material is prohibited on passenger vessel's	Transport document description	: UN2198 Phosphorus pentafluoride, 2.3
Transport hazard class(es) (DOT) : 2.3 - Class 2.3 - Poisonous gas 49 CFR 173.115 Hazard labels (DOT) : 2.3 - Poison gas B - Corrosvie Image: Construction of the	UN-No.(DOT)	: UN2198
Hazard labels (DOT) : 2.3 - Poison gas B - Corrosive Image: Corrosive Image: Corrosive: Corosive: Corrosive: Corosive: Corrosive: Corrosive: Corrosive: Corros	Proper Shipping Name (DOT)	: Phosphorus pentafluoride
B - Corrosive Image: Corrosive DOT Packaging Non Bulk (49 CFR 173.xxx) : 302,304 DOT Packaging Bulk (49 CFR 173.xxx) : 314,315 DOT Special Provisions (49 CFR 172.102) : 2 - This material is poisonous by inhalation (see 171.8 of this subchapter) in Hazard Zom (see 173.13(a) of this subchapter), and must be described as an inhalatic hazard under the provisions of this subchapter). B3 - Bottom outlets are not authorized. B3 - Bottom outlets are not authorized. B4 - Each bulk packaging, except a tank car or a multi-unit-tank car tank, must be insite with an installing material so that the overall thermal conductance at 15.5 C (60 F) is no than 1.5333 kilojoules per hour per square meter per degree Celsus (0.075 Btu per hour ysquare toot per degree Fahrenheit) temperature differential. Insulating materials must no struct our per degree Fahrenheit temperature differential. Insulating materials must no promote corrosion to steel when wet. DOT Packaging Exceptions (49 CFR 173.xxx) : None DOT Quantity Limitations Passenger aircraft/rail : Forbidden OT Quantity Limitations Cargo aircraft only (49 : Forbidden OT Vessel Stowage Location : D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel in which the limiting number of passengers is exceeded. DOT Vessel Stowage Other : 125;173 Other information available : 125;173 Other information available : 125;173	Transport hazard class(es) (DOT)	: 2.3 - Class 2.3 - Poisonous gas 49 CFR 173.115
DOT Packaging Non Bulk (49 CFR 173.xxx) : 302;304 DOT Packaging Buk (49 CFR 173.xxx) :: 314;315 DOT Special Provisions (49 CFR 172.102) :: 2 - This material is poisonous by inhalation (see 171.8 of this subchapter), in Hazard Zom (see 173.116(a) or 173.133(a) of this subchapter), and must be described as an inhalatic hazard under the provisions of this subchapter). B9 - Bottom outlets are not authorized. B9 - Bottom outlets are not authorized. B0 - Type Comparison of this an insulating materials to that the overall thermad conductance at 15.5 C (60 F) is no tran 1.5333 kilojoules per hour per square meter per degree Celsius (0.075 Btu per hour) us square foot per degree Fahrenheily temperature differential. Insulating materials must no promote corrosion to steel when wet. DOT Quantity Limitations Passenger aircraft/rail : Forbidden CFR 173.77) DOT Vessel Stowage Location : D - The material must be stowed "on deck only" on a cargo vessel and on a passenger or passengers per gene per sender by uses length, but the material is prohibited on passen DOT Vessel Stowage Other : 40 - Stow "clear of inving quarters" Emergency Response Guide (ERG) Number : 125;173 Other information available : 2198 Proper Shipping Name (IMDG) : 2198 Proper Shipping Name (IATA) : 2198 Proper Shipping Name (IATA) : 2198 Proper Shipping Name (IATA) : 2198	Hazard labels (DOT)	5
DOT Packaging Bulk (49 CFR 173.xxx) : 314.315 DOT Special Provisions (49 CFR 172.102) : 2 This material is polsonous by inhalation (see 171.8 of this subchapter), and must be described as an inhalatic hazard under the provisions of this subchapter). BOT Special Provisions (49 CFR 172.102) : 2 This material is polsonous by inhalation (see 171.8 of this subchapter), and must be described as an inhalatic hazard under the provisions of this subchapter). BOT Special Provisions (49 CFR 173.xxx) : Dotto multi-unit-tank car tank, must be insuit with an insulating material os that the overall themal conductance at 15, 5 C (60 F) is no than 1.5333 kilojoules per hour per square meter per degree Celsius (0.075 Btu per hour square foot per degree Fahrenheit) temperature differential. Insulating materials is nust no promote corroson to steel when wet. DOT Quantity Limitations Cargo aircraft only (49 : Forbidden : Forbidden CFR 175.70 : D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessels in which the limiting number of passengers is exceeded. DOT Vessel Stowage Other : 40 - Stow "clear of living quarters" Emergency Response Guide (ERG) Number : 125.173 Other information : No supplementary information available. Transport by sea : 2 - Gases Air transport : 2 - Gases Air transport UNNo. (IATA) : 2 198 Proper Shipping Name (IATA) : 2 198		HAZARD
DOT Special Provisions (49 CFR 172.102) 2 - This material is poisonous by inhalation (see 171.8 of this subchapter), and must be described as an inhalatic hazard under the provisions of this subchapter), and must be described as an inhalatic hazard under the provisions of this subchapter). B9 - Bottom outlets are not authorized. B14 - Each bulk packaging, except a tank car or a multi-unit-tank car tank, must be insult with an insulating material so that the overall thermal conductance at 15.5 C (60 F) is no than 1.533 kiloidules per hour per square metr prodegree Celsus (0.075 Btu per hour square foot per degree Fahrenheit) temperature differential. Insulating materials must no promote corrosion to steel when wet. DOT Packaging Exceptions (49 CFR 173.xxx) : None DOT Quantity Limitations Passenger aircraft/rail : Forbidden CFR 175.75) : D - The material must be stowed "on deck only" on a cargo vessel and on a passenger or passenger per each 3 m of overall vessel length, but the material is prohibited on passen vessels in which the limiting number of passengers is exceeded. DOT Vessel Stowage Other : 40 - Stow "clear of living quarters" Emergency Response Guide (ERG) Number : 125;173 Other information available : 2198 Proper Shipping Name (IMDG) : 2 198 Proper Shipping Name (IATA) : 2	DOT Packaging Non Bulk (49 CFR 173.xxx)	: 302;304
(see 173.116(a) or 173.133(a) of this subchapter), and must be described as an inhalatic hazard under the provisions of this subchapter), and must be described as an inhalatic hazard under the provisions of this subchapter. B9 - Bottom outlets are not authorized. 	DOT Packaging Bulk (49 CFR 173.xxx)	: 314;315
DOT Quantity Limitations Passenger aircraft/rail : Forbidden (49 CFR 173.27) DOT Quantity Limitations Cargo aircraft only (49) : Forbidden CFR 175.75) DOT Vessel Stowage Location : D - The material must be stowed "on deck only" on a cargo vessel and on a passenger or passenger per each 3 m of overall vessel length, but the material is prohibited on passen vessels in which the limiting number of passengers is exceeded. DOT Vessel Stowage Other : 40 - Stow "clear of living quarters" Emergency Response Guide (ERG) Number : 125;173 Other information : No supplementary information available. TDG No additional information available Transport by sea UN-No. (IMDG) : 2198 Proper Shipping Name (IMDG) : 2198 Proper Shipping Name (IATA) : 2198	DOT Special Provisions (49 CFR 172.102)	B9 - Bottom outlets are not authorized. B14 - Each bulk packaging, except a tank car or a multi-unit-tank car tank, must be insulated with an insulating material so that the overall thermal conductance at 15.5 C (60 F) is no more than 1.5333 kilojoules per hour per square meter per degree Celsius (0.075 Btu per hour per square foot per degree Fahrenheit) temperature differential. Insulating materials must not
(49 CFR 173.27) The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel Stowage Location DOT Vessel Stowage Location : D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel is mich the limiting number of passengers is invested the limiting number of passengers is exceeded. DOT Vessel Stowage Other : 40 - Stow "clear of living quarters" Emergency Response Guide (ERG) Number : 125;173 Other information : No supplementary information available. TTG No additional information available : Transport by sea : 2198 Proper Shipping Name (IMDG) : 2 - Gases Air transport : 2 - Gases Air transport : 2 - Gases Air transport Shipping Name (IATA) : 2 198 Proper Shipping Name (IATA) : 2 198	DOT Packaging Exceptions (49 CFR 173.xxx)	: None
CFR 175.75) D - The material must be stowed "on deck only" on a cargo vessel and on a passenger or passenger per each 3 m of overall vessel length, but the material is prohibited on passenger or vessels in which the limiting number of passengers is exceeded. DOT Vessel Stowage Other : 40 - Stow "clear of living quarters" Emergency Response Guide (ERG) Number : 125;173 Other information : No supplementary information available. TDG No additional information available Transport by sea UN-No. (IMDG) UN-No. (IMDG) : 2198 Proper Shipping Name (IMDG) : 2 - Gases Air transport UN-No. (IATA) UN-No. (IATA) : 2 198 Proper Shipping Name (IATA) : 2 198		: Forbidden
carrying a number of passengers limited to not more than the larger of 25 passengers or passenger per each 3 m of overall vessel length, but the material is prohibited on passen vessels in which the limiting number of passengers is exceeded.DOT Vessel Stowage Other: 40 - Stow "clear of living quarters"Emergency Response Guide (ERG) Number: 125;173Other information: No supplementary information available.TDG No additional information available:Transport by sea UN-No. (IMDG): 2198Proper Shipping Name (IMDG): 2198Air transport UN-No. (IATA): 2198Proper Shipping Name (IATA): 2198		: Forbidden
Emergency Response Guide (ERG) Number : 125;173 Other information : No supplementary information available. TDG No additional information available Transport by sea . UN-No. (IMDG) : 2198 Proper Shipping Name (IMDG) : PHOSPHORUS PENTAFLUORIDE Class (IMDG) : 2 - Gases Air transport . . UN-No. (IATA) : 2198 Proper Shipping Name (IATA) : 2 - Gases Air transport . . UN-No. (IATA) : 2 198 Proper Shipping Name (IATA) : 2 198	DOT Vessel Stowage Location	: D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded.
Other information : No supplementary information available. TDG No additional information available Transport by sea UN-No. (IMDG) : 2198 Proper Shipping Name (IMDG) : PHOSPHORUS PENTAFLUORIDE Class (IMDG) : 2 - Gases Air transport UN-No. (IATA) Proper Shipping Name (IATA) : 2198 Proper Shipping Name (IATA) : 2198 Proper Shipping Name (IATA) : 2198	DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"
TDG No additional information available Transport by sea UN-No. (IMDG) : 2198 Proper Shipping Name (IMDG) : PHOSPHORUS PENTAFLUORIDE Class (IMDG) : 2 - Gases Air transport UN-No. (IATA) Proper Shipping Name (IATA) : 2198 Proper Shipping Name (IATA) : 2198 Proper Shipping Name (IATA) : 2198	Emergency Response Guide (ERG) Number	: 125;173
No additional information available Transport by sea UN-No. (IMDG) : 2198 Proper Shipping Name (IMDG) : PHOSPHORUS PENTAFLUORIDE Class (IMDG) : 2 - Gases Air transport UN-No. (IATA) Proper Shipping Name (IATA) : 2198	Other information	: No supplementary information available.
Transport by sea UN-No. (IMDG) : 2198 Proper Shipping Name (IMDG) : PHOSPHORUS PENTAFLUORIDE Class (IMDG) : 2 - Gases Air transport UN-No. (IATA) Proper Shipping Name (IATA) : 2198 Proper Shipping Name (IATA) : 2198 Class (IATA) : 2198	TDG	
UN-No. (IMDG): 2198Proper Shipping Name (IMDG): PHOSPHORUS PENTAFLUORIDEClass (IMDG): 2 - GasesAir transportUN-No. (IATA): 2198Proper Shipping Name (IATA): 2198Class (IATA): Phosphorus pentafluorideClass (IATA): 2	No additional information available	
Proper Shipping Name (IMDG) : PHOSPHORUS PENTAFLUORIDE Class (IMDG) : 2 - Gases Air transport	Transport by sea	
Class (IMDG) : 2 - Gases Air transport UN-No. (IATA) UN-No. (IATA) : 2198 Proper Shipping Name (IATA) : Phosphorus pentafluoride Class (IATA) : 2	. ,	: 2198
Air transport UN-No. (IATA) : 2198 Proper Shipping Name (IATA) : Phosphorus pentafluoride Class (IATA) : 2	Proper Shipping Name (IMDG)	: PHOSPHORUS PENTAFLUORIDE
UN-No. (IATA): 2198Proper Shipping Name (IATA): Phosphorus pentafluorideClass (IATA): 2	Class (IMDG)	: 2 - Gases
Proper Shipping Name (IATA) : Phosphorus pentafluoride Class (IATA) : 2	Air transport	
Class (IATA) : 2	UN-No. (IATA)	: 2198
	Proper Shipping Name (IATA)	: Phosphorus pentafluoride
	Class (IATA)	: 2
SECTION 15: Regulatory information	SECTION 15: Regulatory information	
15.1. US Federal regulations		

Phosphorus pentafluoride (7647-19-0) Listed on the United States TSCA (Toxic Substances Control Act) inventory

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

Phosphorus pentafluoride (7647-19-0)

Listed on the Canadian NDSL (Non-Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Phosphorus pentafluoride (7647-19-0)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the Canadian IDL (Ingredient Disclosure List)

Listed on INSQ (Mexican national Inventory of Chemical Substances)

15.3. US State regulations	regulations
----------------------------	-------------

Phosphorus pentafluoride (7647-19-0)
State or local regulations

U.S. - New Jersey - Right to Know Hazardous Substance List

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

SECTION 16: Other information

Full text of H-phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhalation) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Liquefied gas	Gases under pressure Liquefied gas
Simple Asphy	Simple Asphyxiant
Skin Corr. 1B	Skin corrosion/irritation Category 1B
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H280	Contains gas under pressure; may explode if heated
H301	Toxic if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H331	Toxic if inhaled
H335	May cause respiratory irritation
H380	May displace oxygen and cause rapid suffocation

NFPA health hazard


NFPA fire hazard

NFPA reactivity

: 4 - Very short exposure could cause death or serious residual injury even though prompt medical attention was given.

: 0 - Materials that will not burn.

: 2 - Normally unstable and readily undergo violent decomposition but do not detonate. Also: may react violently with water or may form potentially explosive mixtures with water.



Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

HMIS III Rating	
Health	: 4 Severe Hazard - Life-threatening, major or permanent damage may result from single or repeated overexposures
Flammability	: 0 Minimal Hazard - Materials that will not burn
Physical	: 2 Moderate Hazard - Materials that are unstable and may undergo violent chemical changes at normal temperature and pressure with low risk for explosion. Materials may react violently with water or form peroxides upon exposure to air.

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.