

### Safety Data Sheet M016203

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 01/12/2017 Version: 1.0

### **SECTION 1: Identification**

### Identification

: Substance Product form Substance name Thionyl fluoride CAS No. 7783-42-8 Product code M016-2-03 Formula : F2OS

Synonyms Sulfurooyl difluoride : MFCD00040328 Other means of identification

#### Relevant identified uses of the substance or mixture and uses advised against

: Laboratory chemicals Use of the substance/mixture

Manufacture of substances

Scientific research and development

### Details of the supplier of the safety data sheet

SynQuest Laboratories, Inc.

P.O. Box 309

Alachua, FL 32615 - United States of America

T (386) 462-0788 - F (386) 462-7097

info@synquestlabs.com - www.synquestlabs.com

### **Emergency telephone number**

Emergency number : (844) 523-4086 (3E Company - Account 10069)

### SECTION 2: Hazard(s) identification

### Classification of the substance or mixture

#### Classification (GHS-US)

Simple Asphy H380 - May displace oxygen and cause rapid suffocation Liquefied gas H280 - Contains gas under pressure; may explode if heated

Acute Tox. 4 (Oral) H302 - Harmful if swallowed H310 - Fatal in contact with skin Acute Tox. 1 (Dermal) H330 - Fatal if inhaled

Acute Tox. 1 (Inhalation)

H314 - Causes severe skin burns and eye damage Skin Corr. 1B

Eve Dam. 1 H318 - Causes serious eve damage STOT SE 3 H335 - May cause respiratory irritation

Full text of H-phrases: see section 16

### **Label elements**

## **GHS-US** labeling

Hazard pictograms (GHS-US)

Precautionary statements (GHS-US)



GHS05





GHS06

GHS07

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) H280 - Contains gas under pressure: may explode if heated

H302 - Harmful if swallowed

H310+H330 - Fatal in contact with skin or if inhaled H314 - Causes severe skin burns and eye damage

H335 - May cause respiratory irritation

H380 - May displace oxygen and cause rapid suffocation P260 - Do not breathe fumes, gas, mist, spray, vapors

P262 - Do not get in eyes, on skin, or on clothing

P264 - Wash skin thoroughly after handling

P270 - Do not eat, drink or smoke when using this product P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P284 - In case of inadequate ventilation wear respiratory protection

P301+P312 - If swallowed: Call a POISON CENTER or doctor/ physician if you feel unwell

SDS ID: M016203 01/12/2017 EN (English US) Page 1

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/ physician

P320 - Specific treatment is urgent (see supplemental first aid instructions on this label)

P321 - Specific treatment (see supplemental first aid instructions on this label)

P330 - Rinse mouth

P361 - Take off immediately all contaminated clothing

P363 - Wash contaminated clothing before reuse

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P405 - Store locked up

P410+P403 - Protect from sunlight. Store in a well-ventilated place

P501 - Dispose of contents/container to an approved waste disposal plant

### 2.3. Other hazards

Other hazards not contributing to the classification

: May cause frostbite.

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Substance type : Mono-constituent

Name	Product identifier	%	Classification (GHS-US)
Thionyl fluoride (Main constituent)	(CAS No) 7783-42-8	<= 100	Simple Asphy, H380 Liquefied gas, H280 Acute Tox. 4 (Oral), H302 Acute Tox. 1 (Dermal), H310 Acute Tox. 1 (Inhalation), H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335

Full text of H-phrases: see section 16

#### 3.2. Mixture

Not applicable

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

First-aid measures general

: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Move the affected personnel away from the contaminated area.

First-aid measures after inhalation

: Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Get immediate medical advice/attention.

First-aid measures after skin contact

Thaw frosted parts with lukewarm water. Do no rub affected area. Remove contaminated clothing and shoes. In case of skin contact, wearing rubber gloves rub 2.5% calcium gluconate gel continuously into the affected area for 1.5 hours or until further medical care is available. Get immediate medical advice/attention.

First-aid measures after eye contact

: Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention. Immediately flush eyes thoroughly with water for at least 15 minutes.

First-aid measures after ingestion

: Due to its physical form, exposure to this chemical is not likely. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get immediate medical advice/attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries

: The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.

Symptoms/injuries after inhalation

: May cause drowsiness or dizziness. Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.

Symptoms/injuries after skin contact

: Contact with the liquid the may cause cold burns/frostbite.

Symptoms/injuries after eye contact : Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to frostbite from rapid liquid evaporation.

01/12/2017 EN (English US) SDS ID: M016203 2/8

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Absorption of excessive F- can result in acute systemic fluorosis with hypocalcemia, interference with various metabolic functions and organ damage (heart, liver, kidneys).

### **SECTION 5: Firefighting measures**

#### 5.1 **Extinguishing media**

Suitable extinguishing media

: Alcohol resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing media appropriate for surrounding fire.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard

: Thermal decomposition generates: Hydrogen fluoride. Sulfur oxides.

Explosion hazard

Risk of explosion if heated under confinement. Use water spray or fog for cooling exposed

containers.

Reactivity

Reacts with water, generates gases or heat. Reacts on exposure to water with some metals to

release highly explosive/flammable hydrogen gas.

#### Advice for firefighters

Firefighting instructions

: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection during firefighting

Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".

### **SECTION 6: Accidental release measures**

### Personal precautions, protective equipment and emergency procedures

General measures

: Evacuate unnecessary personnel. Ensure adequate air ventilation. May cause suffocation by reducing oxygen available for breathing. Do not breathe gas, fumes, vapor or spray.

#### 6.1.1. For non-emergency personnel

**Emergency procedures** 

: Only qualified personnel equipped with suitable protective equipment may intervene.

### For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

**Emergency procedures** 

Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level.

#### **Environmental precautions**

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment

: Stop leak if safe to do so.

Methods for cleaning up

Ventilate area.

Other information

: For disposal of solid materials or residues refer to section 13: "Disposal considerations".

### Reference to other sections

No additional information available

### **SECTION 7: Handling and storage**

### Precautions for safe handling

Additional hazards when processed

: Pressurized container: Do not pierce or burn, even after use. Close valve after each use and when empty.

Precautions for safe handling

: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, gas, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes.

Safe handling of the gas receptacle

Securely chain cylinders when in use and protect against physical damage.

Hygiene measures

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### Conditions for safe storage, including any incompatibilities

Technical measures

: Comply with applicable regulations.

Storage conditions

Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep container closed when not in use. Moisture sensitive.

Incompatible materials

: Refer to Section 10 on Incompatible Materials.

Prohibitions on mixed storage

: Do not store with: Acids.

01/12/2017 EN (English US) SDS ID: M016203 3/8

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Storage area : Store in dry, cool, well-ventilated area.

## SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

No additional information available

### 8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers

should be available in the immediate vicinity of any potential exposure. Systems under pressure should be regularily checked for leakage. Oxygen detectors should be used when asphyxiating gases may be released. Gas detectors should be used when toxic gases may be

released.

Hand protection : Protective gloves. 29 CFR 1910.138: Hand Protection.

Eye protection : Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory

Protection.

Thermal hazard protection : Cold insulating gloves.

Other information : Safety shoes. 29 CFR 1910.136: Foot Protection.

### SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Gas

Color : No data available
Odor : No data available
Odor threshold : No data available
pH : No data available

Melting point : -129 °C

Freezing point : No data available Boiling point : -43 - -38 °C Flash point : No data available Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) No data available : No data available **Explosion limits** : No data available Explosive properties Oxidizing properties : No data available 155 psig (@ 24 °C) Vapor pressure Relative density No data available Relative vapor density at 20 °C : No data available Specific gravity / density : 1.758 g/ml (@ 25 °C)

Molecular mass 86.06 g/mol : No data available Solubility : No data available Log Pow Auto-ignition temperature No data available Decomposition temperature No data available Viscosity : No data available : No data available Viscosity, kinematic Viscosity, dynamic : No data available

#### 9.2. Other information

No additional information available

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Reacts with water, generates gases or heat. Reacts on exposure to water with some metals to release highly explosive/flammable hydrogen gas.

01/12/2017 EN (English US) SDS ID: M016203 4/8

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 10.2. Chemical stability

The product is stable at normal handling and storage conditions.

### 10.3. Possibility of hazardous reactions

Contact with acids liberates toxic gas. Contact with water liberates toxic gas.

#### 10.4. Conditions to avoid

Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep away from heat, sparks and flame.

#### 10.5. Incompatible materials

Acids. Glass. Strong bases. Strong oxidizing agents. Water.

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

### **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed. Dermal: Fatal in contact with skin. Inhalation: Fatal if inhaled.

Skin corrosion/irritation : Causes severe skin burns and eye damage.

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : May cause respiratory irritation.

Specific target organ toxicity (repeated

exposure)

: Not classified

Aspiration hazard : Not classified

Potential Adverse human health effects and

symptoms

Absorption of excessive F- can result in acute systemic fluorosis with hypocalcemia, interference with various metabolic functions and organ damage (heart, liver, kidneys).

Symptoms/injuries after inhalation

: May cause drowsiness or dizziness. Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.

Symptoms/injuries after skin contact

Symptoms/injuries after eye contact

: Contact with the liquid the may cause cold burns/frostbite.

: Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to frostbite from rapid liquid evaporation.

### **SECTION 12: Ecological information**

#### 12.1. Toxicity

No additional information available

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

No additional information available

### SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.

Waste disposal recommendations : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Recycle the material as far as possible.

01/12/2017 EN (English US) SDS ID: M016203 5/8

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### **SECTION 14: Transport information**

### **Department of Transportation (DOT)**

In accordance with DOT

Transport document description : UN3162 Liquefied gas, toxic, n.o.s. Inhalation Hazard Zone B, 2.3

UN-No.(DOT) : UN3162

Proper Shipping Name (DOT) : Liquefied gas, toxic, n.o.s. Inhalation Hazard Zone B Transport hazard class(es) (DOT) : 2.3 - Class 2.3 - Poisonous gas 49 CFR 173.115

Hazard labels (DOT) : 2.3 - Poison gas



DOT Packaging Non Bulk (49 CFR 173.xxx) : 304 DOT Packaging Bulk (49 CFR 173.xxx) : 314;315

DOT Symbols : G - Identifies PSN requiring a technical name

DOT Special Provisions (49 CFR 172.102) : 2 - This material is poisonous by inhalation (see 171.8 of this subchapter) in Hazard Zone B (see 173.116(a) or 173.133(a) of this subchapter), and must be described as an inhalation

hazard under the provisions of this subchapter.

B9 - Bottom outlets are not authorized.

B14 - Each bulk packaging, except a tank car or a multi-unit-tank car tank, must be insulated with an insulating material so that the overall thermal conductance at 15.5 C (60 F) is no more than 1.5333 kilojoules per hour per square meter per degree Celsius (0.075 Btu per hour per square foot per degree Fahrenheit) temperature differential. Insulating materials must not

promote corrosion to steel when wet.

DOT Packaging Exceptions (49 CFR 173.xxx) : None
DOT Quantity Limitations Passenger aircraft/rail : Forbidden

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : Forbidden

CFR 175.75)

DOT Vessel Stowage Location : D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel

carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger

vessels in which the limiting number of passengers is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Other information : No supplementary information available.

### **TDG**

No additional information available

### Transport by sea

UN-No. (IMDG) : 3162

Proper Shipping Name (IMDG) : LIQUEFIED GAS, TOXIC, N.O.S.

Class (IMDG) : 2 - Gases

Air transport

UN-No. (IATA) : 3162

Proper Shipping Name (IATA) : Liquefied gas, toxic, n.o.s.

Class (IATA) : 2

### **SECTION 15: Regulatory information**

### 15.1. US Federal regulations

### Thionyl fluoride (7783-42-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

01/12/2017 EN (English US) SDS ID: M016203 6/8

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

### 15.2. International regulations

### **CANADA**

Thionyl fluoride (7783-42-8)		
Listed on the Canadian NDSL (Non-Domestic Substances List)		
WHMIS Classification	Class A - Compressed Gas Class E - Corrosive Material	

### **EU-Regulations**

No additional information available

### **National regulations**

### Thionyl fluoride (7783-42-8)

Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on the Canadian IDL (Ingredient Disclosure List)

### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

### **SECTION 16: Other information**

### Full text of H-phrases:

Acute Tox. 1 (Dermal)	Acute toxicity (dermal) Category 1	
Acute Tox. 1 (Inhalation)	Acute toxicity (inhalation) Category 1	
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4	
Eye Dam. 1	Serious eye damage/eye irritation Category 1	
Liquefied gas	Gases under pressure Liquefied gas	
Simple Asphy	Simple Asphyxiant	
Skin Corr. 1B	Skin corrosion/irritation Category 1B	
STOT SE 3	Specific target organ toxicity (single exposure) Category 3	
H280	Contains gas under pressure; may explode if heated	
H302	Harmful if swallowed	
H310	Fatal in contact with skin	
H314	Causes severe skin burns and eye damage	
H318	Causes serious eye damage	
H330	Fatal if inhaled	
H335	May cause respiratory irritation	
H380	May displace oxygen and cause rapid suffocation	

NFPA health hazard

: 4 - Very short exposure could cause death or serious residual injury even though prompt medical attention was given.

NFPA fire hazard

: 0 - Materials that will not burn.

NFPA reactivity

: 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.

**HMIS III Rating** 

Health

: 4 Severe Hazard - Life-threatening, major or permanent damage may result from single or repeated overexposures

Flammability

: 0 Minimal Hazard - Materials that will not burn

Physical

: 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo

hazardous polymerization in the absence of inhibitors.

SDS US (GHS HazCom 2012)

01/12/2017 SDS ID: M016203 EN (English US) 7/8

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.

01/12/2017 EN (English US) SDS ID: M016203 8/8