

Safety Data Sheet M053207

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 06/07/2017 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Substance

Substance name : Iodine heptafluoride

 CAS No
 : 16921-96-3

 Product code
 : M053-2-07

 Formula
 : F7I

Synonyms : Iodine(VII) fluoride
Other means of identification : MFCD25978139

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Laboratory chemicals

Manufacture of substances

Scientific research and development

1.3. Details of the supplier of the safety data sheet

SynQuest Laboratories, Inc.

P.O. Box 309

Alachua, FL 32615 - United States of America

T (386) 462-0788 - F (386) 462-7097

info@synquestlabs.com - www.synquestlabs.com

1.4. Emergency telephone number

Emergency number : (844) 523-4086 (3E Company - Account 10069)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Simple Asphy H380 - May displace oxygen and cause rapid suffocation

Ox. Gas 1 H270 - May cause or intensify fire; oxidizer

Liquefied gas H280 - Contains gas under pressure; may explode if heated

Acute Tox. 3 (Oral) H301 - Toxic if swallowed Acute Tox. 3 (Dermal) H311 - Toxic in contact with skin

Acute Tox. 1 (Inhalation:gas) H330 - Fatal if inhaled

Skin Corr. 1A H314 - Causes severe skin burns and eye damage

STOT SE 3 H335 - May cause respiratory irritation

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



GHS03

GHS04







Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H270 - May cause or intensify fire; oxidizer

H280 - Contains gas under pressure; may explode if heated H301+H311 - Toxic if swallowed or in contact with skin H314 - Causes severe skin burns and eye damage

H330 - Fatal if inhaled

H335 - May cause respiratory irritation

H380 - May displace oxygen and cause rapid suffocation

Precautionary statements (GHS-US) : P220 - Keep/Store away from combustible materials

P244 - Keep reduction valves/valves and fittings free from oil and grease

P260 - Do not breathe fumes, gas, mist, spray, vapors

P264 - Wash skin thoroughly after handling

P270 - Do not eat, drink or smoke when using this product P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves/protective clothing/eye protection/face protection

06/13/2017 EN (English US) SDS ID: M053207 Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P284 - In case of inadequate ventilation wear respiratory protection P301+P310 - If swallowed: Immediately call a poison center/doctor/...

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting

P302+P352 - If on skin: Wash with plenty of soap and water

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/physician

P363 - Wash contaminated clothing before reuse P370+P376 - In case of fire: Stop leak if safe to do so

P403 - Store in a well-ventilated place

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P405 - Store locked up

P410+P403 - Protect from sunlight. Store in a well-ventilated place

P501 - Dispose of contents/container to an approved waste disposal plant

Other hazards

Other hazards not contributing to the classification

: Contact with acids liberates toxic gas. Contact with water liberates toxic gas.

Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

Substance

Substance type : Mono-constituent

Name	Product identifier	%	Classification (GHS-US)
lodine heptafluoride (Main constituent)	(CAS No) 16921-96-3	<= 100	Simple Asphy, H380 Ox. Gas 1, H270 Liquefied gas, H280 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 1 (Inhalation:gas), H330 Skin Corr. 1A, H314 STOT SE 3. H335

Full text of H-phrases: see section 16

Mixture

Not applicable

SECTION 4: First aid measures

Description of first aid measures

First-aid measures general

: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Move the affected personnel away from the contaminated area.

First-aid measures after inhalation Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Get immediate medical advice/attention.

First-aid measures after skin contact Thaw frosted parts with lukewarm water. Do no rub affected area. Remove contaminated clothing and shoes. In case of skin contact, wearing rubber gloves rub 2.5% calcium gluconate gel continuously into the affected area for 1.5 hours or until further medical care is available.

Get immediate medical advice/attention.

: Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical First-aid measures after eye contact advice/attention. Immediately flush eyes thoroughly with water for at least 15 minutes.

First-aid measures after ingestion Due to its physical form, exposure to this chemical is not likely. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get immediate medical advice/attention.

Most important symptoms and effects, both acute and delayed

: The most important known symptoms and effects are described in the labelling (see section Symptoms/injuries 2.2) and/or in section 11.

Symptoms/injuries after inhalation May cause drowsiness or dizziness. Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.

Symptoms/injuries after skin contact : Contact with the liquid the may cause cold burns/frostbite.

Symptoms/injuries after eye contact Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to frostbite from rapid liquid evaporation.

06/13/2017 EN (English US) SDS ID: M053207 2/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Absorption of excessive F- can result in acute systemic fluorosis with hypocalcemia, interference with various metabolic functions and organ damage (heart, liver, kidneys).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide. Dry powder. Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : Do not use extinguishing media containing water.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Thermal decomposition generates: Carbon oxides. Hydrogen fluoride. Hydrogen iodide.

Explosion hazard : Contains gas under pressure; may explode if heated. Use water spray or fog for cooling

exposed containers.

5.3. Advice for firefighters

Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection during firefighting : Wear gas tight chemically protective clothing in combination with self contained breathing

apparatus. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate unnecessary personnel. Ensure adequate air ventilation. May cause suffocation by

reducing oxygen available for breathing. Do not breathe gas, fumes, vapor or spray.

6.1.1. For non-emergency personnel

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground

level.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so.

Methods for cleaning up : Ventilate area.

Other information : For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Close valve after each use and

when empty.

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Ensure good

ventilation of the work station. Do not breathe fumes, gas, mist, spray, vapors. Wear personal

protective equipment. Avoid contact with skin and eyes.

Safe handling of the gas receptacle : Securely chain cylinders when in use and protect against physical damage.

Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or

smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep container closed

when not in use. Moisture sensitive.

Incompatible materials : Refer to Section 10 on Incompatible Materials.

Prohibitions on mixed storage : Do not store with: Acids. Water.

Storage area : Store in dry, cool, well-ventilated area.

06/13/2017 EN (English US) SDS ID: M053207 3/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers

should be available in the immediate vicinity of any potential exposure. Systems under pressure should be regularily checked for leakage. Oxygen detectors should be used when asphyxiating gases may be released. Gas detectors should be used when toxic gases may be

released.

Hand protection : Protective gloves. 29 CFR 1910.138: Hand Protection.

Eye protection : Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory

Protection.

Thermal hazard protection : Cold insulating gloves.

Other information : Safety shoes. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas

Color : No data available
Odor : No data available
Odor threshold : No data available
pH : No data available

Melting point : 4.5 °C

Freezing point : No data available

Boiling point : 4.8 °C

Flash point : No data available : No data available Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) : No data available **Explosion limits** No data available Explosive properties : No data available : No data available Oxidizing properties : No data available Vapor pressure Relative density : No data available Relative vapor density at 20 °C No data available Specific gravity / density : 2.7 g/ml (@ 25 °C) Molecular mass : 259.89 a/mol Solubility No data available Log Pow : No data available : No data available Auto-ignition temperature Decomposition temperature No data available Viscosity No data available Viscosity, kinematic No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Viscosity, dynamic

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

06/13/2017 EN (English US) SDS ID: M053207 4/8

: No data available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.3. Possibility of hazardous reactions

Reacts violently with water.

10.4. Conditions to avoid

Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep away from heat, sparks and flame.

10.5. Incompatible materials

Bases. Combustible materials. Glass. Halogenated hydrocarbons. Halogens. Metals. Metal oxides. Reducing agents. Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Toxic if swallowed. Dermal: Toxic in contact with skin. Inhalation:gas: Fatal if inhaled.

Iodine heptafluoride (16921-96-3)		
ATE US (oral)	100.000 mg/kg body weight	
ATE US (dermal)	300.000 mg/kg body weight	
ATE US (gases)	10.000 ppmV/4h	

Skin corrosion/irritation : Causes severe skin burns and eye damage.

Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : May cause respiratory irritation.

Specific target organ toxicity (repeated : Not classified

exposure)

Aspiration hazard : Not classified

Potential Adverse human health effects and

symptoms

Absorption of excessive F- can result in acute systemic fluorosis with hypocalcemia, interference with various metabolic functions and organ damage (heart, liver, kidneys).

Symptoms/injuries after inhalation : May cause drowsiness or dizziness. Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.

Symptoms/injuries after skin contact : Contact with the liquid the may cause cold burns/frostbite.

Symptoms/injuries after eye contact : Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due

to frostbite from rapid liquid evaporation.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.

06/13/2017 EN (English US) SDS ID: M053207 5/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Waste disposal recommendations

: Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information

: Recycle the material as far as possible.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN3307 Liquefied gas, toxic, oxidizing, n.o.s. (Inhalation Hazard Zone B), 2.3

UN-No.(DOT) : UN3307

Proper Shipping Name (DOT) : Liquefied gas, toxic, oxidizing, n.o.s.

Inhalation Hazard Zone B

Transport hazard class(es) (DOT) : 2.3 - Class 2.3 - Poisonous gas 49 CFR 173.115

Hazard labels (DOT) 2.3 - Poison gas 5.1 - Oxidizer



DOT Packaging Non Bulk (49 CFR 173.xxx)

DOT Packaging Bulk (49 CFR 173.xxx)

DOT Symbols

DOT Special Provisions (49 CFR 172.102)

: 314;315

: G - Identifies PSN requiring a technical name

: 2 - This material is poisonous by inhalation (see 171.8 of this subchapter) in Hazard Zone B (see 173.116(a) or 173.133(a) of this subchapter), and must be described as an inhalation

hazard under the provisions of this subchapter.

B9 - Bottom outlets are not authorized. B14 - Each bulk packaging, except a tank car or a multi-unit-tank car tank, must be insulated with an insulating material so that the overall thermal conductance at 15.5 C (60 F) is no more than 1.5333 kilojoules per hour per square meter per degree Celsius (0.075 Btu per hour per

square foot per degree Fahrenheit) temperature differential. Insulating materials must not promote corrosion to steel when wet.

DOT Packaging Exceptions (49 CFR 173.xxx)

DOT Quantity Limitations Passenger aircraft/rail : Forbidden

(49 CFR 173.27)

: None

DOT Quantity Limitations Cargo aircraft only (49 : Forbidden

CFR 175.75)

: D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel **DOT Vessel Stowage Location** carrying a number of passengers limited to not more than the larger of 25 passengers or one

passenger per each 3 m of overall vessel length, but the material is prohibited on passenger

vessels in which the limiting number of passengers is exceeded.

DOT Vessel Stowage Other 40 - Stow "clear of living quarters"

Other information : No supplementary information available.

TDG

No additional information available

Transport by sea

UN-No. (IMDG) : 3307

: LIQUEFIED GAS. TOXIC. OXIDIZING, N.O.S. Proper Shipping Name (IMDG)

Class (IMDG) : 2 - Gases

Air transport

UN-No. (IATA) : 3307

Proper Shipping Name (IATA) : Liquefied gas, toxic, oxidizing, n.o.s.

Class (IATA) : 2

06/13/2017 EN (English US) SDS ID: M053207 6/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

Iodine heptafluoride (16921-96-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

Iodine heptafluoride (16921-96-3)

Listed on the Canadian NDSL (Non-Domestic Substances List)

EU-Regulations

No additional information available

National regulations

lodine heptafluoride (16921-96-3)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Japanese ISHL (Industrial Safety and Health Law)

Listed on the Korean ECL (Existing Chemicals List)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

SECTION 16: Other information

Full text of H-phrases:

Acute Tox. 1 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 1	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3	
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3	
Liquefied gas	Gases under pressure Liquefied gas	
Ox. Gas 1	Oxidizing gases Category 1	
Simple Asphy	Simple Asphyxiant	
Skin Corr. 1A	Skin corrosion/irritation Category 1A	
STOT SE 3	Specific target organ toxicity (single exposure) Category 3	
H270	May cause or intensify fire; oxidizer	
H280	Contains gas under pressure; may explode if heated	
H301	Toxic if swallowed	
H311	Toxic in contact with skin	
H314	Causes severe skin burns and eye damage	
H330	Fatal if inhaled	
H335	May cause respiratory irritation	
H380	May displace oxygen and cause rapid suffocation	

NFPA health hazard

 4 - Very short exposure could cause death or serious residual injury even though prompt medical attention was given.

NFPA fire hazard

: 0 - Materials that will not burn.


NFPA reactivity

 2 - Normally unstable and readily undergo violent decomposition but do not detonate. Also: may react violently with water or may form potentially explosive

mixtures with water.

NFPA specific hazard

: OX - This denotes an oxidizer, a chemical which can greatly increase the rate of combustion/fire.



06/13/2017 EN (English US) SDS ID: M053207 7/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

HMIS III Rating

Health : 4 Severe Hazard - Life-threatening, major or permanent damage may result from single or

repeated overexposures

Flammability : 0 Minimal Hazard - Materials that will not burn

Physical : 2 Moderate Hazard - Materials that are unstable and may undergo violent chemical changes at

normal temperature and pressure with low risk for explosion. Materials may react violently with

water or form peroxides upon exposure to air.

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.

06/13/2017 EN (English US) SDS ID: M053207 8/8